



A selection of products for  
**OUTDOOR REMOVAL OF  
TAGGING/GRAFFITI**



**CLEANING SOLUTIONS FROM BLUE AND GREEN**

Blue & Green AB | Phone. + 46 418 399 000 | E-mail: [info@blueandgreen.se](mailto:info@blueandgreen.se) | [www.blueandgreen.se](http://www.blueandgreen.se)



A dirty facade full of graffiti sends a negative signal. Therefore, most businesses and individuals want their facades to be clean, attractive, and well-maintained. At the same time, most people also know that proper cleaning and treatment can extend the lifespan of the facade.

### Choose the right product

The surface, material, type, and condition of the facade determine the type of treatment required. With our extensive range of products, we cover virtually all types of facade cleaning, washing, impregnation, and after-treatment.

### Impregnation

In addition to effective products for facade cleaning, we also offer products for impregnating facades. Impregnation minimizes future soiling, making facades more resistant and easier to keep clean.

### Graffiti and tagging

When it comes to graffiti removal, you have several options. The choice of product depends, among other things, on the surface and the type of graffiti.

Our graffiti products are specially developed to remove even stubborn graffiti on delicate surfaces with solid shadows. All our products are as gentle as possible.

We have graffiti products that protect the cleaned surface, making it easier to remove any new graffiti.

### General

**There should be access to quick and abundant eye flushing near the workplace. For further information and a description of first aid measures, refer to the specific safety data sheet.**

**Use prescribed personal protective equipment.**



## Facades

### Graffiti Remover Tectyl M



### For removal of Tectyl on smooth and porous surfaces covered with thick layers of Tectyl (underbody coatin).

This is an environmentally friendly Tectyl remover that can be used on most stone and metal surfaces.

#### How to use it

##### Smooth surfaces:

- For extensive graffiti/tags, apply *Graffiti Remover Tectyl M* with a brush or low-pressure sprayer.
- Let it work on the surface from 5 minutes to 30 minutes. The reaction time depends on weather conditions, age, and characteristics.
- Do not let it dry.
- With mechanical processing, such as brushing, the reaction time can be reduced.
- Rinse off with hot water (60-70 °C) under moderate pressure. Neutralize with *Eco Wash Green* cleaner in a 1:10 mixture.

##### Porous surfaces:

- Apply *Graffiti Remover Tectyl M* with a low-pressure sprayer or brush.
- Let it penetrate the surface for a few minutes. The reaction time varies depending on weather conditions, the age of the tag, and temperature.
- Rinse with hot water under high pressure, 70-90 °C, pressure depending on the surface's characteristics, approximately 50-200 bar.
- Repeat the treatment as needed.

Item number: 339005 – 5L  
339010 – 10L  
339200 – 200L

## Graffiti Remover Eden Gel



A highly potent, combined graffiti and shadow remover designed for specific use in cold weather or challenging removal situations. It is used outdoors and is primarily suitable for porous surfaces.

**Graffiti Remover Eden Gel** is a lightly thickened graffiti remover designed primarily for use on porous surfaces such as granite, brick, limestone, concrete, tiles, glazed brick, and treated marble. It effectively dissolves spray paint and markers, etc.

**Note!** *Graffiti Remover Eden Gel* should not be used on soft metals such as aluminum. Always conduct a test in case of uncertainty.

### How to use it

- Apply *Graffiti Remover Eden Gel* with a brush.
- Work the product thoroughly into the surface.
- Allow it to work until the graffiti is dissolved, approximately 10-30 minutes, depending on the surface, graffiti/tag, and weather conditions.
- Rinse off with high-pressure hot water, 90°C, 150 bar, or adjust it according to the surface's nature. The nozzle angle should be 15°-25°, and the water flow approximately 20 liters per minute.
- If there are "shadows" remaining, reapply *Graffiti Remover Eden Gel*, let it work for about 10 minutes before high-pressure rinsing. You can also use *Graffiti Remover Shadow* (separate section).

Item number: 026010 – 10L

## Graffiti Remover Dracula



A highly potent liquid, combined graffiti- and shadow remover.

**Graffiti Remover Dracula** is a tag/graffiti remover designed primarily for use on porous surfaces such as granite, brick, limestone, concrete, tiles, glazed brick, and treated marble. It effectively dissolves spray paint and markers and is intended for tagging or single-layer graffiti.

**Note!** *Graffiti Remover Dracula* should not be used on soft metals such as aluminum. Always perform a test in case of uncertainty.

### How to use it

- Apply *Graffiti Remover Dracula* with a brush.
- Work the product thoroughly into the surface.
- Allow it to work until the tag/graffiti is dissolved, approximately 10-30 minutes, depending on the surface, tag, and weather conditions.
- Rinse off with high-pressure hot water, 90°C, 150 bar, or adjust it according to the surface's nature. The nozzle angle should be 15°-25°, and the water flow approximately 20 liters per minute.
- If there are "shadows" remaining, apply *Graffiti Remover Shadow* (separate section), let it work for about 5-10 minutes before high-pressure rinsing. Repeat as needed.

Item number: 333005 – 5L  
333025 – 25L



# Facades

## Graffiti Remover Blue Gel



For removing tags and graffiti on porous surfaces such as granite, brick, concrete, treated marble, and limestone. It is also suitable for hard surfaces like tiles and glazed brick.

**Graffiti Remover Blue Gel** is a thick, highly effective graffiti remover. It is primarily used on porous surfaces but also works on smooth, hard surfaces. It efficiently dissolves spray paint, markers, etc., and performs well on tectyl.

It can be used on the following substrates:

- **Porous surfaces:** Concrete, brick, granite, marble, limestone, sandstone, slate, surfaces painted with inorganic paint.
- **Hard surfaces:** Metal, treated wood, tiles, glazed brick, as well as certain plastic materials.

### How to use it

- Apply BG GR Blue Gel with a brush or paint sprayer.
- Work the product thoroughly into the surface.
- Allow it to work until the Tag/graffiti is dissolved, approximately 20 minutes to 4 hours. Rinse off with high-pressure hot water, 90°C, 150 bar, or adjust it according to the surface's nature. The nozzle angle should be 15°-25°, and the water flow approximately 20 liters per minute.
- If there are "shadows" remaining, use *Graffiti Remover Shadow* (separate section), let it work for about 5-10 minutes before high-pressure rinsing. Repeat as needed.

**NOTE!** On metal surfaces, the effectiveness may diminish if too much pressure is applied. In such cases, rinsing and working with a sponge or cloth may be more effective than high-pressure washing.

Item number: 330005 – 5L  
330015 – 15L

## Graffiti Remover Shadow



Use to remove lingering shadows during graffiti cleaning. It is applied outdoors, primarily on porous surfaces.

**Graffiti Remover Shadow** removes "remaining shadows" in connection with graffiti removal. BG GR Shadow is used on the following materials: granite, gneiss, limestone, concrete, tiles, glazed brick, treated marble, and wood, as well as inorganic paint.

**NOTE!** Skal ikke brukes på myke metaller som for eksempel aluminium.

### How to use it

- Apply *Graffiti Remover Shadow* with a brush or applicator. Let it work for approximately 2-30 minutes or until the graffiti is dissolved. Rinse off with high-pressure hot water, 90°C, 150 bar, or adjust it according to the surface's nature. The nozzle angle should be 15°-25°, and the water flow approximately 20 liters per minute.

**NOTE!** On metal surfaces, the effectiveness may be reduced if too much pressure is used. Rinsing and working with a sponge or cloth may yield better results than high-pressure washing. Repeat the treatment if shadows persist.

Item number: 355005 – 5L  
355025 – 25L  
355600 – 600L



## Graffiti Remover Kilroy



**Thin-flowing acidic graffiti- and shadow remover.**

**Graffiti Remover Kilroy** is a highly effective product for the removal of challenging and stubborn colors and shadows.

**NOTE!** Use *Graffiti Remover Kilroy* only on surfaces that can withstand acids.

### How to use it

- Apply *Graffiti Remover Kilroy* to the graffiti/shadows and let it work for 1-5 minutes.
- Rinse off with a temperature and pressure suitable for the surface.
- Repeat if necessary.

Item number: 313010 – 10L

## Soft Wash Hypo



**A specially developed remover for challenging pigmented shadows from ink and aniline colors. Suitable for both indoor and outdoor use, primarily on porous surfaces.**

**Soft Wash Hypo** is a remover that lightens challenging pigmented shadows from ink and aniline colors. It can also lighten shadows left by spray graffiti. It can be used on most light porous surfaces.

**NOTE!** When uncertain about bleaching, always perform a test on a small area. Use Hypo with caution on metals, as they may be affected. Contains Hypochlorite - Liquid.

### How to use it

- Apply Softwash HYPO to the surface,
- Repeat if necessary. This also applies to highly absorbent surfaces.
- The dwell time may vary, and reapplication during the process may be necessary.
- It can be mixed with foam for better adhesion on vertical surfaces.
- Rinse afterward with lukewarm or hot water. Adjust the pressure according to the surface.

**NOTE! MUST NOT BE MIXED WITH ACIDS, AS IT MAY RELEASE TOXIC FUMES! SHAKE THE CONTAINER BEFORE USE.**

Shelf life: Approximately 6-9 months in unopened packaging.

Item number: 362020 – 20L



# Painted/lacquered surfaces

## Graffiti Remover 21 Liquid & Graffiti Remover 21 Gel



**Use for removal of tagging on hard and lacquered surfaces. They can be used both indoors and outdoors. Available in liquid and gel forms.**

**Graffiti Remover 21** is used for the removal of tag/graffiti, primarily on smooth, industrially painted surfaces. It can also be used on porous surfaces. It is suitable for both outdoor and indoor use.

It is used for removing tagging and paint on smooth, industrially painted surfaces such as trains, buses, cars, sheet metal buildings, smooth constructions, etc. It can also be used on porous surfaces.

### How to use it

#### Graffiti removal on smooth surfaces:

- Apply a thick layer of *Graffiti Remover 21 Gel* or use the liquid form with a brush over the graffiti,

- Work on the surface for a maximum of 15 minutes until the graffiti/paint is dissolved.
- Rinse off with hot water under high pressure (70-90°C, 100-150 bar).
- In some cases, like on trains/metro, cold water and a water hose can also be used.
- Apply a new layer if necessary and follow the instructions.

#### Graffiti removal on porous surfaces:

- Apply *Graffiti Remover 21 Gel* or liquid with a brush, paint sprayer or brush.
- Work the product well into the surface.
- Let it sit until the graffiti is dissolved, approximately 20 minutes to 4 hours.
- Rinse off with hot water under high pressure (90°C, 150 bar) or adjust it according to the surface's nature. The nozzle's spreading angle should be 15°-25°, and the water flow approximately 20 liters per minute.
- If there are "shadows" remaining, use *Graffiti Remover Shadow* or *Ink Remover Shadow*.


**NOTE!** On metal surfaces, the effectiveness may diminish if too much pressure is used. Rinsing and working with a brush or similar may yield better results than high-pressure washing.

#### Graffiti Remover 21 Flytande

Art.nr: 336006 – 5L  
336010 – 10L  
336025 – 25L  
336700 – 1000L

#### Graffiti Remover 21 Gel

Art.nr: 336005 – 5L  
336026 – 25L  
336011 – 10L





## Ink Remover



**A specially developed graffiti remover for challenging ink- and aniline colors. It also dissolves fresh spray paint. Suitable for both indoor and outdoor use.**

**Ink Remover** effectively removes challenging ink and aniline colors, as well as spray paint. It can be used on most surfaces, including hard painted surfaces, porous surfaces, and galvanized surfaces. It has proven to be highly effective in removing aniline colors.

### How to use it

For hard, non-absorbent surfaces:

- Apply *Ink Remover* to a clean cloth.

- Work on removing tags/ink and address the graffiti to avoid streaks, etc.
- For challenging objects, let *Ink Remover* sit for a few minutes before wiping.
- To avoid chemical residues on the surface, neutralize with water or a mild cleaner such as *Aquo Universal* or *Glass Cleaner Blue*.

For porous surfaces with fresh graffiti:

- Apply *Ink Remover* with a low-pressure sprayer.
- Let it sit for a few minutes, then rinse with high-pressure hot water, approximately 90°C, depending on the surface.

Alternatively

- Apply *Ink Remover* with a low-pressure sprayer, let it sit for a few minutes.

or apply *Graffiti Remover Dracula*  
or *Graffiti Remover Eden Gel*

let it work until the graffiti is dissolved.

- Then rinse with high-pressure hot water, approximately 90°C, depending on the surface.
- For pigmented shadows, use *Graffiti Remover Shadow* or internal *Ink Remover Shadow*.

**NOTE!** In case of uncertainty, always perform a test on a small section of the surface.

Art.nr: 3832003 – 1L  
3832005 – 5L

## Light tag-/Graffiti removal

**2 simple and hassle-free products. One in liquid form with a trigger and one in wipes (towels). For general removal, typically suitable for janitorial use.**

Art.nr: 384056 – STK – Wipes  
253005 – 5L – Dunk  
3871046 – 0,5L – Trigger





## Experts in cleaning agents for the professional market

We have one of the market's widest product ranges – and with many years of experience in both development, production and sales of effective cleaning products – which we sell to the European market. The head office is in Sweden, with sales offices in Denmark and Norway as well as an extensive network of dealers.

### Philosophy

Blue & Green aims to deliver products of the highest quality at the right price - with the least possible environmental impact. We have a great focus on the environmental impact when we develop and produce our product range. It is important to us that our products are efficient in our customers application with the least environmental impact.

That is why we have several different environmental labels on a large part of our products and that we are ISO certified. At the same time we are connected to the Swedish circular packaging system, as we think it is crucial to recycle our packaging so that our products impact to the environment has as little impact as possible.

### More information about our products

You will find more products on our website. Or contact us for more information.

<https://blueandgreen.se/en/produkter/>

