

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Alkalisk Micro
DL 2051

Product no.

-

REACH registration number

Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Degreaser

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

Blue & Green AB
Stenorsvägen 52
261 44 Landskrona
Sweden
Tfn: +46 418 399000
Fax: +46 418 13199
www.blueandgreen.se

E-mail

info@blueandgreen.se

SDS date

2020-10-22

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Asp. Tox. 1; H304

Skin Irrit. 2; H315

Eye Dam. 1; H318

See full text of H-phrases in section 2.2.

2.2. Label elements

Hazard pictogram(s)**Signal word**

Danger

Hazard statement(s)

May be fatal if swallowed and enters airways. (H304)

Causes skin irritation. (H315)

According to EC-Regulation 2015/830

Causes serious eye damage. (H318)

Precautionary statements

General If medical advice is needed, have product container or label at hand. (P101).
Keep out of reach of children. (P102).

Prevention Wear eye protection. (P280).

Response IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338).

Storage Store locked up. (P405).

Disposal Dispose of contents/container to an approved waste disposal plant. (P501).

Identity of the substances primarily responsible for the major health hazards

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics; 1-Heptanol, 2-propyl-, 5EO; 2-Ethylhexanol, ethoxylated; Quaternary, ammonium, compounds, C12-14-alkyl, hydroxyethyl, dimethyl, ethoxylated, chlorides

Additional labelling

Not applicable

Unique formula identifier (UFI)

-

2.3. Other hazards

This product contains substances that can cause chemical pneumonia if inhaled. The symptoms of chemical pneumonia may appear after several hours.

Additional warnings

Tactile warning. If this product is sold in retail, it must be delivered with child-resistant fastening.

VOC (volatile organic compound)

Not applicable

SECTION 3: Composition/information on ingredients

3.1/3.2. Substances/Mixtures

NAME:	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
IDENTIFICATION NOS.:	EC-no: 918-481-9 REACH-no: 01-2119457273-39
CONTENT:	10 - <15%
CLP CLASSIFICATION:	Asp.Tox.1;H304
NOTE:	O
NAME:	1-Heptanol, 2-propyl-, 5EO
IDENTIFICATION NOS.:	CAS-no: 160875-66-1
CONTENT:	5 - <10%
CLP CLASSIFICATION:	Eye Dam. 1 H318
NAME:	2-Ethylhexanol, ethoxylated
IDENTIFICATION NOS.:	CAS-no: 26468-86-0 EC-no: 607-943-2
CONTENT:	5 - <10%
CLP CLASSIFICATION:	Eye Dam. 1 H318
NAME:	Quaternary, ammonium, compounds, C12-14-alkyl, hydroxyethyl, dimethyl, ethoxylated, chlorides
IDENTIFICATION NOS.:	CAS-no: 1554325-20-0 EC-no: 810-152-7
CONTENT:	2.5 - <5%
CLP CLASSIFICATION:	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Aquatic Acute 1 H302, H315, H318, H400 (M-acute = 1)
NAME:	2-(2-butoxyethoxy)ethanol
IDENTIFICATION NOS.:	CAS-no: 112-34-5 EC-no: 203-961-6 REACH-no: 01-2119475104-44 Index-no: 603-096-00-8
CONTENT:	1 - <2.5%
CLP CLASSIFICATION:	Eye Irrit. 2 H319
NOTE:	L
NAME:	Alcohols C12-14, ethoxylated 3EO
IDENTIFICATION NOS.:	CAS-no: 68439-50-9 EC-no: 932-106-6
CONTENT:	1 - <2.5%
CLP CLASSIFICATION:	Eye Irrit. 2, Aquatic Acute 1, Aquatic Chronic 3 H319, H400, H412 (M-acute = 1)

According to EC-Regulation 2015/830

NAME:	sodium hydroxide
IDENTIFICATION NOS.:	CAS-no: 1310-73-2 EC-no: 215-185-5 REACH-no: 01-2119457892-27 Index-no: 011-002-00-6
CONTENT:	0.25 - <1%
CLP CLASSIFICATION:	Met. Corr. 1, Skin Corr. 1A, Eye Dam. 1 H290, H314, H318

(*) O = Organic solvent L = European occupational exposure limit. See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

ATEmix(oral) > 2000
 Eye Cat. 1 Sum = Sum(Ci/S(G)CLi) = 5.296 - 7.944
 Skin Cat. 2 Sum = Sum(Ci/S(G)CLi) = 1.7328 - 2.5992
 N chronic (CAT 4) Sum = Sum(Ci/(M(chronic)ⁱ*25)*0.1*10^{CAT4}) = 0.04928 - 0.07392
 N acute (CAT 1) Sum = Sum(Ci/M(acute)ⁱ*25) = 0.1664 - 0.2496

Detergent:
 15 - 30%: NON-IONIC SURFACTANTS
 5 - 15%: ALIPHATIC HYDROCARBONS
 < 5%: CATIONIC SURFACTANTS

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service: Dial 0344 892 0111 (24 h service). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with soap and water.

Eye contact

Remove contact lenses. Flush eyes with plenty of water or salt water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing.

Ingestion

Do not induce vomiting! If vomiting occurs, keep head facing down to prevent vomit entering the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should be kept under medical attention for a minimum of 48 hours.

Burns

Not applicable

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if inhaled. The symptoms of chemical pneumonia may appear after several hours.

This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned: Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist.

5.2. Special hazards arising from the substance or mixture

Nothing special

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

According to EC-Regulation 2015/830

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances. Avoid inhalation of vapours from spilled material.

6.2. Environmental precautions

No specific requirements.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, storage of tobacco, consumption and storage of food or liquids are not allowed in the workrooms. See section on 'Exposure controls/personal protection' for information on personal protection. Avoid direct contact with the product.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Storage temperature

Room temperature 18 to 23°C

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL

sodium hydroxide

Long-term exposure limit (8-hour TWA reference period): - ppm | - mg/m³

Short-term exposure limit (15-minute reference period): - ppm | 2 mg/m³

2-(2-butoxyethoxy)ethanol

Long-term exposure limit (8-hour TWA reference period): 10 ppm | 67,5 mg/m³

Short-term exposure limit (15-minute reference period): 15 ppm | 101.2 mg/m³

DNEL / PNEC

DNEL (2-(2-butoxyethoxy)ethanol): 83 mg/kg

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (2-(2-butoxyethoxy)ethanol): 67.5 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (2-(2-butoxyethoxy)ethanol): 67.5 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - Workers

DNEL (2-(2-butoxyethoxy)ethanol): 5 mg/kg bw/d

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-(2-butoxyethoxy)ethanol): 50 mg/kg bw/d

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-(2-butoxyethoxy)ethanol): 40.5 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - General population

DNEL (2-(2-butoxyethoxy)ethanol): 101.2 mg/m³

Exposure: Inhalation

Duration of Exposure: Short term – Local effects - Workers

DNEL (2-(2-butoxyethoxy)ethanol): 40.5 mg/m³

Exposure: Inhalation

According to EC-Regulation 2015/830

Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-(2-butoxyethoxy)ethanol): 60.7 mg/m³

Exposure: Inhalation

Duration of Exposure: Short term – Local effects - General population

DNEL (sodium hydroxide): 1 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - General population

DNEL (sodium hydroxide): 1 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - Workers

DNEL (sodium hydroxide): 2 mg/kg bw/d

Exposure: Dermal

Duration of Exposure: Short term – Local effects - Workers

DNEL (sodium hydroxide): 2 mg/m³

Exposure: Inhalation

Duration of Exposure: Short term – Local effects - Workers

PNEC (2-(2-butoxyethoxy)ethanol): 200 mg/l

Exposure: Sewage Treatment Plant

PNEC (2-(2-butoxyethoxy)ethanol): 0.44 mg/kg dw

Exposure: Marine water sediment

PNEC (2-(2-butoxyethoxy)ethanol): 4.4 mg/kg dw

Exposure: Freshwater sediment

PNEC (2-(2-butoxyethoxy)ethanol): 1 mg/l

Exposure: Freshwater

PNEC (2-(2-butoxyethoxy)ethanol): 0.1 mg/l

Exposure: Marine water

PNEC (2-(2-butoxyethoxy)ethanol): 3.9 mg/l

Exposure: Intermittent release

PNEC (2-(2-butoxyethoxy)ethanol): 0.32 mg/kg dw

Exposure: Soil

8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

General recommendations

Observe general occupational hygiene standards.

Exposure scenarios

There is no appendix to this safety data sheet.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

Keep containment materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

According to EC-Regulation 2015/830



Generally

Use only CE marked protective equipment.

Respiratory Equipment

NA

Skin protection

Dedicated work clothing should be worn. Wear a protective suit in the event of prolonged periods of work with the product.

Hand protection

Nitrile rubber

Breakthrough time: > 480 minutes (Class 6)

Eye protection

Wear safety glasses with side shields.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form	Liquid
Colour	Yellowish
Odour	Petroleum
Odour threshold (ppm)	No data available.
pH	13
Viscosity (40°C)	No data available.
Density (g/cm ³)	0.99

Phase changes

Melting point (°C)	No data available.
Boiling point (°C)	No data available.
Vapour pressure	No data available.
Decomposition temperature (°C)	No data available.
Evaporation rate (n-butylacetate = 100)	No data available.

Data on fire and explosion hazards

Flash point (°C)	No data available.
Ignition (°C)	No data available.
Auto flammability (°C)	No data available.
Explosion limits (% v/v)	No data available.
Explosive properties	No data available.

Solubility

Solubility in water	Soluble
n-octanol/water coefficient	No data available.

9.2. Other information

Solubility in fat (g/L)	No data available.
-------------------------	--------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

10.3. Possibility of hazardous reactions

Nothing special

10.4. Conditions to avoid

Nothing special

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

According to EC-Regulation 2015/830

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Substance: sodium hydroxide

Species: Rat

Test: LD50

Route of exposure: Oral

Result: 325 mg/kg bw

Substance: Alcohols C12-14, ethoxylated 3EO

Species: Rat

Test: LD50

Route of exposure: Oral

Result: >2000 mg/kg

Substance: Alcohols C12-14, ethoxylated 3EO

Species: Rabbit

Test: LD50

Route of exposure: Dermal

Result: >2000 mg/kg

Substance: 2-(2-butoxyethoxy)ethanol

Species: Rat

Test: LD50

Route of exposure: Oral

Result: >2000 mg/kg

Substance: 2-(2-butoxyethoxy)ethanol

Species: Rabbit

Test: LD50

Route of exposure: Dermal

Result: 2764 mg/kg

Substance: 2-(2-butoxyethoxy)ethanol

Species: Rat

Test: LC50

Route of exposure: Inhalation

Result: >29 ppm 2h

Substance: 2-(2-butoxyethoxy)ethanol

Species: Mouse

Test: LD50

Route of exposure: Oral

Result: 2410 mg/kg

Substance: Quaternary, ammonium, compounds, C12-14-alkyl, hydroxyethyl, dimethyl, ethoxylated, chlorides

Species: Rat

Test: LD50

Route of exposure: Oral

Result: >300-2000 mg/kg

Substance: 2-Ethylhexanol, ethoxylated

Species: Rat

Test: LD50

Route of exposure: Oral

Result: >2000 mg/kg

Substance: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Species: Rat

Test: LD50

Route of exposure: Oral

Result: >5000mg/kg

Substance: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Species: Rabbit

Test: LD50

Route of exposure: Dermal

Result: >5000 mg/kg

Substance: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

According to EC-Regulation 2015/830

Species: Rat
 Test: LC50
 Route of exposure: Inhalation
 Result: 4951 mg/m³, 4h

Skin corrosion/irritation

Causes skin irritation.

Data on substance: 2-(2-butoxyethoxy)ethanol
 Test: OECD Guideline 404
 Organism: Rabbit
 Result: not irritating

Serious eye damage/irritation

Causes serious eye damage.

Data on substance: 2-(2-butoxyethoxy)ethanol
 Test: OECD Guideline 404
 Organism: Rabbit
 Result: irritating

Respiratory or skin sensitisation

Data on substance: 2-(2-butoxyethoxy)ethanol
 Test: OECD Guideline 406
 Organism: Guinea pig
 Result: Negative

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

No data available.

STOT-repeated exposure

No data available.

Aspiration hazard

May be fatal if swallowed and enters airways.

Long term effects

This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

SECTION 12: Ecological information

12.1. Toxicity

Substance: sodium hydroxide
 Species: Fish
 Test: LC50
 Duration: 96h
 Result: 33-189 mg/l

Substance: sodium hydroxide
 Species: Daphnia
 Test: EC50
 Duration: 48h
 Result: 40-240 mg/l

Substance: Alcohols C12-14, ethoxylated 3EO
 Species: Daphnia
 Test: EC50
 Duration: 48h
 Result: 0.1-1mg/l

Substance: Alcohols C12-14, ethoxylated 3EO
 Species: Fish
 Test: LC50
 Duration: 96h
 Result: 0.1-1 mg/l

Substance: Alcohols C12-14, ethoxylated 3EO
 Species: Algae
 Test: EC50
 Duration: 72h
 Result: 0.1-1 mg/l

Substance: 2-(2-butoxyethoxy)ethanol
 Species: Fish

According to EC-Regulation 2015/830

Test: LC50
Duration: 96h
Result: >100 mg/l

Substance: 2-(2-butoxyethoxy)ethanol
Species: Algae
Test: EC50
Duration: 96h
Result: >100 mg/l

Substance: 2-(2-butoxyethoxy)ethanol
Species: Daphnia
Test: EC50
Duration: 48h
Result: >100 mg/l

Substance: Quaternary, ammonium, compounds, C12-14-alkyl, hydroxyethyl, dimethyl, ethoxylated, chlorides
Species: Fish
Test: LC50
Duration: 96h
Result: 10-100 mg/l

Substance: Quaternary, ammonium, compounds, C12-14-alkyl, hydroxyethyl, dimethyl, ethoxylated, chlorides
Species: Daphnia
Test: EC50
Duration: 48h
Result: 1-10 mg/l

Substance: Quaternary, ammonium, compounds, C12-14-alkyl, hydroxyethyl, dimethyl, ethoxylated, chlorides
Species: Algae
Test: EC50
Duration: 72h
Result: 1-10 mg/l

Substance: 2-Ethylhexanol, ethoxylated
Species: Fish
Test: LC50
Duration: 96h
Result: 10-100 mg/l

Substance: 2-Ethylhexanol, ethoxylated
Species: Daphnia
Test: EC50
Duration: 48h
Result: 1-10 mg/l

Substance: 2-Ethylhexanol, ethoxylated
Species: Algae
Test: EC50
Duration: 72h
Result: 1-10 mg/l

Substance: 1-Heptanol, 2-propyl-, 5EO
Species: Fish
Test: LC50
Duration: 96h
Result: 10-100 mg/l

Substance: 1-Heptanol, 2-propyl-, 5EO
Species: Daphnia
Test: EC50
Duration: 48h
Result: 10-100 mg/l

Substance: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Species: Fish
Test: LC50
Duration: 96h
Result: >1000mg/l

Substance: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Species: Algae
Test: EC50

According to EC-Regulation 2015/830

Duration: 72h
Result: >1000mg/l

Substance: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Species: Daphnia
Test: EC50
Duration: 48h
Result: >1000mg/l

12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
sodium hydroxide	Yes	No data available	No data available
Alcohols C12-14, ethoxylated ...	Yes	CO2 Evolution Test	>60%
2-(2-butoxyethoxy)ethanol	Yes	Modified OECD	100%
Quaternary, ammonium, compounds, ...	Yes	Screening Test	>60%
2-Ethylhexanol, ethoxylated	Yes	Closed Bottle Test	>60%
1-Heptanol, 2-propyl-, 5EO	Yes	CO2 Evolution Test	>60%
Hydrocarbons, C10-C13, n-alkan...	Yes	Closed Bottle Test	80
		CO2 Evolution Test	

12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BCF
sodium hydroxide	No	No data available	No data available
Alcohols C12-14, ethoxylated ...	No	No data available	No data available
2-(2-butoxyethoxy)ethanol	No	1	No data available
Quaternary, ammonium, compounds, ...	No	No data available	No data available
2-Ethylhexanol, ethoxylated	No	No data available	No data available
1-Heptanol, 2-propyl-, 5EO	No	No data available	No data available

12.4. Mobility in soil

2-(2-butoxyethoxy)ethanol: Log Koc= 0.8703, Calculated from LogPow (High mobility potential.).

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.
This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

Waste

EWC code

-

Specific labelling

Not applicable

Contaminated packing

Contaminated packaging must be disposed of similarly to the product.

SECTION 14: Transport information

14.1 – 14.4

Not dangerous goods according to ADR, IATA and IMDG.

ADR/RID

14.1. UN number	-
14.2. UN proper shipping name	-
14.3. Transport hazard class(es)	-
14.4. Packing group	-
Notes	-
Tunnel restriction code	-

IMDG

UN-no.	-
Proper Shipping Name	-
Class	-
PG*	-
EmS	-
MP**	-
Hazardous constituent	-

IATA/ICAO

According to EC-Regulation 2015/830

UN-no. -
 Proper Shipping Name -
 Class -
 PG* -

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product cf. Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Demands for specific education

-

Additional information

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Seveso

-

Biocidal reg. no.

Not applicable

Sources

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.
 The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.
 Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents.
 Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).
 Regulation (EC) 1907/2006 (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H290 - May be corrosive to metals.
 H302 - Harmful if swallowed.
 H304 - May be fatal if swallowed and enters airways.
 H314 - Causes severe skin burns and eye damage.
 H315 - Causes skin irritation.
 H318 - Causes serious eye damage.
 H319 - Causes serious eye irritation.
 H400 - Very toxic to aquatic life.
 H412 - Harmful to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

-

Additional label elements

Not applicable

Other

According to EC-Regulation 2015/830

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on:

The classification of the mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The safety data sheet is validated by

David Löwenstein

Date of last essential change

(First cipher in SDS version)

-

Date of last minor change

(Last cipher in SDS version)

-