

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Degreaser Orange 12

Product no.

-

REACH registration number

Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Degreaser

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

Blue & Green AB

Stenorsvägen 52

261 44 Landskrona

Sweden

Tfn: +46 418 399000

Fax: +46 418 13199

www.blueandgreen.se

E-mail

info@blueandgreen.se

SDS date

2021-03-29

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Flam. Liq. 3; H226

Asp. Tox. 1; H304

Eye Irrit. 2; H319

STOT SE 3; H336

See full text of H-phrases in section 2.2.

2.2. Label elements

Hazard pictogram(s)**Signal word**

Danger

Hazard statement(s)

Flammable liquid and vapour. (H226)

May be fatal if swallowed and enters airways. (H304)

According to EC-Regulation 2015/830

Causes serious eye irritation. (H319)
May cause drowsiness or dizziness. (H336)

Precautionary statements

General If medical advice is needed, have product container or label at hand. (P101).
Keep out of reach of children. (P102).
Prevention Wear eye protection/gloves. (P280).
Response IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310).
Storage Store in a well-ventilated place. Keep cool. (P403+P235).
Disposal Dispose of contents/container to an approved waste disposal plant. (P501).

Identity of the substances primarily responsible for the major health hazards

propan-2-ol; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Additional labelling

Not applicable

Unique formula identifier (UFI)

11M0-1KQX-900S-4A2T

2.3. Other hazards

This product contains substances that can cause chemical pneumonia if inhaled. The symptoms of chemical pneumonia may appear after several hours.

Additional warnings

Tactile warning. If this product is sold in retail, it must be delivered with child-resistant fastening.

VOC (volatile organic compound)

Not applicable

SECTION 3: Composition/information on ingredients

3.1/3.2. Substances/Mixtures

NAME: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics
IDENTIFICATION NOS.: EC-no: 919-857-5 REACH-no: 01-2119463258-33
CONTENT: 40-60%
CLP CLASSIFICATION: Flam. Liq. 3, STOT SE 3, Asp. Tox. 1
H226, H304, H336

NAME: propan-2-ol
IDENTIFICATION NOS.: CAS-no: 67-63-0 EC-no: 200-661-7 REACH-no: 01-2119457558-25 Index-no: 603-117-00-0
CONTENT: 40-60%
CLP CLASSIFICATION: Flam. Liq. 2, STOT SE 3, Eye Irrit. 2
H225, H319, H336
NOTE: O

(*) O = Organic solvent See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

Eye Cat. 2 Sum = $\sum(C_i/S(G)CL_i) = 4 - 6$

Detergent:
> 30%: ALIPHATIC HYDROCARBONS, ISOPROPYL ALCOHOL

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service: Dial 0344 892 0111 (24 h service). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with soap and water.

Eye contact

According to EC-Regulation 2015/830

Remove contact lenses. Flush eyes with plenty of water or salt water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing.

Ingestion

Do not induce vomiting! If vomiting occurs, keep head facing down to prevent vomit entering the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should be kept under medical attention for a minimum of 48 hours.

Burns

Rinse with water until the pain stops then continue to rinse for a further 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if inhaled. The symptoms of chemical pneumonia may appear after several hours.

This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned: Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid inhalation of vapours from spilled material. Avoid direct contact with spilled substances. Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

6.2. Environmental precautions

No specific requirements.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid static electricity. Protect electrical equipment in accordance with current standards. Do not use spark-forming tools.

Smoking, storage of tobacco, consumption and storage of food or liquids are not allowed in the workrooms. See section on 'Exposure controls/personal protection' for information on personal protection. Avoid direct contact with the product.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Storage temperature

Room temperature 18 to 23°C

According to EC-Regulation 2015/830

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL

propan-2-ol

Long-term exposure limit (8-hour TWA reference period): 400 ppm | 999 mg/m³

Short-term exposure limit (15-minute reference period): 500 ppm | 1250 mg/m³

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% a...

Long-term exposure limit (8-hour TWA reference period): 20 ppm | 37 mg/m³

Short-term exposure limit (15-minute reference period): 50 ppm | 92 mg/m³

DNEL / PNEC

DNEL (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics): 208 mg/kg bw/d

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics): 871 mg/m³

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics): 125 mg/kg bw/d

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics): 185 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics): 125 mg/kg bw/d

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

DNEL (propan-2-ol): 319 mg/kg bw/d

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL (propan-2-ol): 89 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (propan-2-ol): 26 mg/kg bw/d

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

DNEL (propan-2-ol): 888 mg/kg bw/d

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (propan-2-ol): 500 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

PNEC (propan-2-ol): 552 mg/kg dw

Exposure: Marine water sediment

PNEC (propan-2-ol): 140.9 mg/l

Exposure: Freshwater

PNEC (propan-2-ol): 28 mg/kg dw

Exposure: Soil

PNEC (propan-2-ol): 140.9 mg/l

Exposure: Marine water

PNEC (propan-2-ol): 140.9 mg/l

Exposure: Intermittent release

PNEC (propan-2-ol): 2251 mg/l

Exposure: Sewage Treatment Plant

According to EC-Regulation 2015/830

PNEC (propan-2-ol): 552 mg/kg dw
Exposure: Freshwater sediment

8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

General recommendations

Observe general occupational hygiene standards.

Exposure scenarios

There is no appendix to this safety data sheet.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

Keep containment materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment



Generally

Use only CE marked protective equipment.

Respiratory Equipment

Recommended: A. Class 1 (low capacity). Brown

Skin protection

Dedicated work clothing should be worn. Wear a protective suit in the event of prolonged periods of work with the product.

Hand protection

Nitrile rubber

Breakthrough time: > 480 minutes (Class 6)

Eye protection

Wear safety glasses with side shields.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form	Liquid
Colour	Colourless
Odour	Characteristic
Odour threshold (ppm)	No data available.
pH	No data available.
Viscosity (40°C)	No data available.
Density (g/cm ³)	0.78
Phase changes	
Melting point (°C)	No data available.
Boiling point (°C)	No data available.
Vapour pressure	No data available.
Decomposition temperature (°C)	No data available.
Evaporation rate (n-butylacetate = 100)	No data available.
Data on fire and explosion hazards	
Flash point (°C)	25
Ignition (°C)	No data available.
Auto flammability (°C)	No data available.
Explosion limits (% v/v)	No data available.
Explosive properties	No data available.

According to EC-Regulation 2015/830

Solubility	
Solubility in water	Soluble
n-octanol/water coefficient	No data available.
9.2. Other information	
Solubility in fat (g/L)	No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

10.3. Possibility of hazardous reactions

Nothing special

10.4. Conditions to avoid

Avoid static electricity. Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Substance: propan-2-ol

Species: Rabbit

Test: LD50

Route of exposure: Dermal

Result: 13900 mg/kg

Substance: propan-2-ol

Species: Rat

Test: LD50

Route of exposure: Oral

Result: 5840 mg/kg

Substance: propan-2-ol

Species: Rat

Test: LC50

Route of exposure: Inhalation

Result: >25 mg/l, 6h ånga

Substance: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Species: Rabbit

Test: LD50

Route of exposure: Dermal

Result: >5000 mg/kg

Substance: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Species: Rat

Test: LD50

Route of exposure: Oral

Result: >5000 mg/kg

Substance: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Species: Rat

Test: LC50

Route of exposure: Inhalation

Result: >5 mg/l 4h

Skin corrosion/irritation

No data available.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

No data available.

Germ cell mutagenicity

No data available.

According to EC-Regulation 2015/830

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

No data available.

Aspiration hazard

May be fatal if swallowed and enters airways.

Long term effects

This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

SECTION 12: Ecological information

12.1. Toxicity

Substance: propan-2-ol

Species: Daphnia

Test: LC50

Duration: 48h

Result: >100 mg/l

Substance: propan-2-ol

Species: Fish

Test: LC50

Duration: 96h

Result: >100 mg/l

Substance: propan-2-ol

Species: Algae

Test: EC50

Duration: 72h

Result: >100mg/l

Substance: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Species: Daphnia

Test: EL0

Duration: 48h

Result: 1000 mg/l

Substance: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Species: Fish

Test: LL50

Duration: 96h

Result: >1000 mg/l

Substance: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Species: Algae

Test: EL50

Duration: 72h

Result: >1000 mg/l

12.2. Persistence and degradability

Substance

propan-2-ol

Hydrocarbons, C9-C11, n-alkane...

Biodegradability

Yes

Yes

Test

No data available

No data available

Result

No data available

No data available

12.3. Bioaccumulative potential

Substance

propan-2-ol

Potential bioaccumulation

No

LogPow

0.05

BCF

No data available

12.4. Mobility in soil

propan-2-ol: Log Koc= 0.117995, Calculated from LogPow (High mobility potential.).

Hydrocarbons, C9-C11, n-alkane...: Log Koc= 2.4541, Calculated from LogPow (Moderate mobility potential.).

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Other adverse effects

Nothing special

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

According to EC-Regulation 2015/830

Waste

EWC code

-

Specific labelling

Not applicable

Contaminated packing

Contaminated packaging must be disposed of similarly to the product.

SECTION 14: Transport information

14.1 – 14.4

This product is within scope of the regulations of transport of dangerous goods.

ADR/RID

14.1. UN number	1993
14.2. UN proper shipping name	FLAMMABLE LIQUID, N.O.S.
14.3. Transport hazard class(es)	3
14.4. Packing group	III
Notes	-
Tunnel restriction code	-

IMDG

UN-no.	1993
Proper Shipping Name	FLAMMABLE LIQUID, N.O.S.
Class	3
PG*	III
EmS	F-E,S-E
MP**	No
Hazardous constituent	-

IATA/ICAO

UN-no.	1993
Proper Shipping Name	FLAMMABLE LIQUID, N.O.S.
Class	3
PG*	III

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product cf. Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Demands for specific education

-

Additional information

Not applicable

Seveso

Seveso III Part 1: P5c

Biocidal reg. no.

Not applicable

Sources

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.
 The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.
 Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents.
 Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on

According to EC-Regulation 2015/830

classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).

Regulation (EC) 1907/2006 (REACH).

The Control of Major Accident Hazards (COMAH) Regulations 2015.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H225 - Highly flammable liquid and vapour.

H226 - Flammable liquid and vapour.

H304 - May be fatal if swallowed and enters airways.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

The full text of identified uses as mentioned in section 1

-

Additional label elements

Not applicable

Other

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on:

The classification of the mixture in regard of physical hazards has been based on experimental data.

The classification of the mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The safety data sheet is validated by

David Löwenstein

Date of last essential change

(First cipher in SDS version)

-

Date of last minor change

(Last cipher in SDS version)

-