

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Degreaser Plus

Product no.

43

Unique formula identifier (UFI)

91SV-MS9J-399Y-C2DM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Degreaser

Uses advised against

No special

1.3. Details of the supplier of the safety data sheet

Company and address

Blue & Green AB

Stenorsvägen 52

261 44 Landskrona

Sweden

+46 418 399000

www.blueandgreen.se

E-mail

info@blueandgreen.se

Revision

24/05/2022

SDS Version

2.0

Date of previous version

01/12/2021 (1.0)

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

▼ 2.1. Classification of the substance or mixture

Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

▼ Hazard statement(s)

May be fatal if swallowed and enters airways. (H304)

Safety statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)

Keep out of reach of children. (P102)

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

▼ **Prevention**

-

Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310)

Do NOT induce vomiting. (P331)

Storage

-

Disposal

Dispose of contents/container to an approved waste disposal plant. (P501)

Hazardous substances

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

2.3. Other hazards

Additional labelling

EUH066, Repeated exposure may cause skin dryness or cracking.

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

SECTION 3: Composition/information on ingredients

▼ **3.2. Mixtures**

Product/substance	Identifiers	% w/w	Classification	Note
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	CAS No.: EC No.: 918-481-9 REACH: 01-2119457273-39 Index No.:	80-95%	EUH066 Asp. Tox. 1, H304	
2-(2-butoxyethoxy)ethanol	CAS No.: 112-34-5 EC No.: 203-961-6 REACH: 01-2119475104-44 Index No.: 603-096-00-8	3-5%	Eye Irrit. 2, H319	[1], [3]
(2-methoxymethylethoxy)propanol	CAS No.: 34590-94-8 EC No.: 252-104-2 REACH: 01-2119450011-60 Index No.:	1-3%		[1]
propan-2-ol	CAS No.: 67-63-0 EC No.: 200-661-7 REACH: Index No.: 603-117-00-0	1-3%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

▼ **Other information**

[1] European occupational exposure limit

[3] According to UK REACH, Annex XVII, the substance is subject to restrictions.

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

▼ Labelling of contents according to Detergents Regulation (EC) No 648/2004

- ≥ 30%
 - Aliphatic hydrocarbons
- < 5%
 - Anionic surfactants

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap.

If skin irritation occurs: Get medical advice/attention.

Eye contact

Upon irritation of the eye: Remove contact lenses and open eyes widely. Flush eyes with water or saline water(20-30°C) for at least 5 minutes. Seek medical assistance and continue flushing during transport.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs.

Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

Burns

Not applicable

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

▼ 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Use sand, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 on "Disposal considerations" in regard of handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

▼ 7.1. Precautions for safe handling

Avoid direct contact with the product.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

Room temperature 18 to 23°C

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

▼ 8.1. Control parameters

—
2-(2-butoxyethoxy)ethanol

Long term exposure limit (8 hours) (ppm): 10

Long term exposure limit (8 hours) (mg/m³): 67,5

Short term exposure limit (15 minutes) (ppm): 15

Short term exposure limit (15 minutes) (mg/m³): 101,2

—
(2-methoxymethylethoxy)propanol

Long term exposure limit (8 hours) (ppm): 50

Long term exposure limit (8 hours) (mg/m³): 308

Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

—
propan-2-ol

Long term exposure limit (8 hours) (ppm): 400

Long term exposure limit (8 hours) (mg/m³): 999

Short term exposure limit (15 minutes) (ppm): 500

Short term exposure limit (15 minutes) (mg/m³): 1250

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

▼ DNEL

(2-methoxymethylethoxy)propanol

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Duration	Route of exposure	DNEL
Long term – Systemic effects - General population	Dermal	121 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	283 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	37.2 mg/m ³
Long term – Systemic effects - Workers	Inhalation	308 mg/kg
Long term – Systemic effects - General population	Oral	36 mg/kg bw/day
2-(2-butoxyethoxy)ethanol		
Duration	Route of exposure	DNEL
Long term – Local effects - Workers	Inhalation	67.5 mg/m ³
Short term – Local effects - Workers	Inhalation	101.2 mg/m ³
Long term – Systemic effects - General population	Oral	6,25 mg/kg bw/day
propan-2-ol		
Duration	Route of exposure	DNEL
Long term – Systemic effects - General population	Dermal	319 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	888 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	89 mg/m ³
Long term – Systemic effects - Workers	Inhalation	500 mg/m ³
Long term – Systemic effects - General population	Oral	26 mg/kg bw/day
▼ PNEC		
(2-methoxymethylethoxy)propanol		
Route of exposure	Duration of Exposure	PNEC
Freshwater		19 mg/L
Freshwater sediment		70.2 mg/kg
Intermittent release		190 mg/L

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Marine water		1.9 mg/L
Marine water sediment		7.02 mg/kg
Sewage treatment plant		4168 mg/L
Soil		2.74 mg/kg
2-(2-butoxyethoxy)ethanol		
Route of exposure	Duration of Exposure	PNEC
Freshwater		1.1 mg/L
Freshwater sediment		4.4 mg/kg dw
Intermittent release		11 mg/L
Marine water		0.11 mg/L
Marine water sediment		0.44 mg/kg dw
Soil		0.32 mg/kg dw
propan-2-ol		
Route of exposure	Duration of Exposure	PNEC
Freshwater		140.9 mg/L
Freshwater sediment		552 mg/kg
Intermittent release		140.9 mg/L
Marine water		140.9 mg/L
Marine water sediment		552 mg/kg
Sewage treatment plant		2251 mg/L
Soil		28 mg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

▼ Generally


Use only UKCA marked protective equipment.

▼ Respiratory Equipment

Type	Class	Colour	Standards
No specific requirements			


Skin protection

Recommended	Type/Category	Standards
Dedicated work clothing should be worn	-	-




Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Butyl	-	> 480	EN374-2, EN374-3, EN388



Eye protection

Type	Standards
Safety glasses with side shields.	EN166



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Yellowish

Odour / Odour threshold

Characteristic

▼ pH

Testing not relevant or not possible due to nature of the product.

▼ Density (g/cm³)

0.8

Kinematic viscosity

Testing not relevant or not possible due to nature of the product.

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

Testing not relevant or not possible due to nature of the product.

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

Testing not relevant or not possible due to nature of the product.

Vapour pressure

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Testing not relevant or not possible due to nature of the product.

Relative vapour density

Testing not relevant or not possible due to nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to nature of the product.

Data on fire and explosion hazards

▼ Flash point (°C)

65

Ignition (°C)

Testing not relevant or not possible due to nature of the product.

Auto flammability (°C)

Testing not relevant or not possible due to nature of the product.

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to nature of the product.

Solubility

Solubility in water

Testing not relevant or not possible due to nature of the product.

n-octanol/water coefficient

Testing not relevant or not possible due to nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to nature of the product.

9.2. Other information

Other physical and chemical parameters

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

No special

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

▼ Acute toxicity

Product/substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Test method	
Species	Rabbit
Route of exposure	Dermal
Test	LD50
Result	>5000 mg/kg
Other information	

Product/substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Test method	

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Species	Rat
Route of exposure	Inhalation
Test	LC50 (4 hours)
Result	4,951 mg/L
Other information	
<hr/>	
Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Species	Rat
Route of exposure	Oral
Test	LD50
Result	>2000 mg/kg
Other information	
<hr/>	
Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Species	Rabbit
Route of exposure	Dermal
Test	LD50
Result	2764 mg/kg
Other information	
<hr/>	
Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Species	Rat
Route of exposure	Inhalation
Test	LC50
Result	>29 ppm
Other information	
<hr/>	
Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Species	Mouse
Route of exposure	Oral
Test	LD50
Result	2410 mg/kg
Other information	
<hr/>	
Product/substance	(2-methoxymethylethoxy)propanol
Test method	
Species	Rat
Route of exposure	Oral
Test	LD50
Result	>5000 mg/kg
Other information	
<hr/>	
Product/substance	(2-methoxymethylethoxy)propanol
Test method	
Species	Rabbit
Route of exposure	Dermal
Test	LD50

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Result 9510 mg/kg

Other information

Product/substance (2-methoxymethylethoxy)propanol

Test method

Species Rat

Route of exposure Inhalation

Test LC50

Result 3.35 mg/L

Other information

Product/substance propan-2-ol

Test method OECD 401

Species Rat

Route of exposure Oral

Test LD50

Result 5840 mg/kg

Other information

Product/substance propan-2-ol

Test method OECD 403

Species Rat

Route of exposure Inhalation

Test LC50

Result >25 mg/L

Other information

Product/substance propan-2-ol

Test method OECD 402

Species Rabbit

Route of exposure Dermal

Test LD50

Result 13900 mg/kg

Other information

Skin corrosion/irritation

Product/substance 2-(2-butoxyethoxy)ethanol

Test method OECD 404

Species Rabbit

Duration

Result No adverse effect observed (Not irritating)

Other information

Serious eye damage/irritation

Product/substance 2-(2-butoxyethoxy)ethanol

Test method OECD 404

Species Rabbit

Duration

Result Adverse effect observed (Irritating)

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Other information

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Product/substance	2-(2-butoxyethoxy)ethanol
Test method	OECD 406
Species	Guinea pig
Result	No adverse effect observed (not sensitising)
Other information	

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Long term effects

No special

Endocrine disrupting properties

No special

Other information

propan-2-ol has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

▼ 12.1. Toxicity

Product/substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Test method	
Species	Fish, <i>Oncorhynchus mykiss</i>
Compartment	
Duration	96 hours
Test	LL0
Result	>1000 mg/l mg/L
Other information	

Product/substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Test method	
Species	Algae, <i>Pseudokirchneriella subcapitata</i>
Compartment	
Duration	72 hours
Test	ELO
Result	>1000 mg/L
Other information	

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Product/substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Test method	
Species	Daphnia, Daphnia magna
Compartment	
Duration	72 hours
Test	EL0
Result	>1000 mg/L
Other information	
Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Species	Fish, Leuciscus idus
Compartment	
Duration	96 hours
Test	LC50
Result	>100 mg/L
Other information	
Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Species	Algae, Scenedesmus subspicatus
Compartment	
Duration	96 hours
Test	EC50
Result	>100 mg/L
Other information	
Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Species	Daphnia, Daphnia magna
Compartment	
Duration	48 hours
Test	EC50
Result	>100 mg/L
Other information	
Product/substance	(2-methoxymethylethoxy)propanol
Test method	
Species	Fish, Poecilia reticulata
Compartment	
Duration	96 hours
Test	LC50
Result	>1000 mg/L
Other information	
Product/substance	(2-methoxymethylethoxy)propanol
Test method	
Species	Daphnia, Daphnia magna
Compartment	
Duration	48 hours

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Test	EC50
Result	1919 mg/L
Other information	
Product/substance	(2-methoxymethylethoxy)propanol
Test method	
Species	Daphnia, Daphnia magna
Compartment	
Duration	22 d
Test	NOEC
Result	0.5 mg/L
Other information	
Product/substance	(2-methoxymethylethoxy)propanol
Test method	
Species	Algae, Pseudokirchneriella subcapitata
Compartment	
Duration	72 hours
Test	EC50
Result	>969 mg/L
Other information	
Product/substance	propan-2-ol
Test method	
Species	Fish
Compartment	
Duration	96 hours
Test	LC50
Result	>100 mg/L
Other information	
Product/substance	propan-2-ol
Test method	
Species	Algae
Compartment	
Duration	8 d
Test	LOEC
Result	1000 mg/L
Other information	
Product/substance	propan-2-ol
Test method	
Species	Daphnia, Daphnia magna
Compartment	
Duration	48 hours
Test	LC50
Result	>100 mg/L
Other information	
Product/substance	propan-2-ol
Test method	

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Species	Algae
Compartment	
Duration	72 hours
Test	EC50
Result	>100 mg/L
Other information	

▼ 12.2. Persistence and degradability

Product/substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Biodegradable	Yes
Test method	
Result	

Product/substance	2-(2-butoxyethoxy)ethanol
Biodegradable	Yes
Test method	OECD 301 E
Result	100%

Product/substance	(2-methoxymethylethoxy)propanol
Biodegradable	Yes
Test method	OECD 301 F
Result	75%

Product/substance	propan-2-ol
Biodegradable	Yes
Test method	
Result	

12.3. Bioaccumulative potential

Product/substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Test method	
Potential bioaccumulation	No
LogPow	No data available
BCF	No data available
Other information	

Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Potential bioaccumulation	No
LogPow	1.0000
BCF	No data available
Other information	

Product/substance	(2-methoxymethylethoxy)propanol
Test method	
Potential bioaccumulation	No
LogPow	0.0060

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

BCF No data available

Other information

Product/substance propan-2-ol

Test method

Potential No

bioaccumulation

LogPow 0.0500

BCF No data available

Other information

12.4. Mobility in soil

(2-methoxymethylethoxy)propanol

LogKoc = 0.28, High mobility potential.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

No special

▼ 12.7. Other adverse effects

No special

SECTION 13: Disposal considerations

▼ 13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

To the extent the material has not been subject to regular tests of peroxide formation the waste shall be treated as explosive waste.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

07 06 04* Other organic solvents, washing liquids and mother liquors

Specific labelling

Not applicable

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

* Packing group

** Environmental hazards

▼ Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

No special

Demands for specific education

No specific requirements

SEVESO - Categories / dangerous substances

Not applicable

▼ Additional information

Tactile warning.

If this product is sold in retail, it must be delivered with child-resistant fastening.

▼ Sources

The Health and Safety at Work etc. Act 1974 Regulations 2013.

Regulation (EC) No 648/2004 on detergents as retained and amended in UK law.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

▼ Full text of H-phrases as mentioned in section 3

EUH066, Repeated exposure may cause skin dryness or cracking.

H225, Highly flammable liquid and vapour.

H304, May be fatal if swallowed and enters airways.

H319, Causes serious eye irritation.

H336, May cause drowsiness or dizziness.

▼ Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

▼ Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

▼ The safety data sheet is validated by

Åsa Möller

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en