SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Glass Cleaner

Product no.

286

Unique formula identifier (UFI)

T1Q5-5X3E-V99C-T78D

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Cleaning liquid

Uses advised against

No special

1.3. Details of the supplier of the safety data sheet

Company and address

Blue & Green AB
Stenorsvägen 52
261 44 Landskrona
Sweden
+46 418 399000
www.blueandgreen.se

E-mail

info@blueandgreen.se

Revision

06/04/2022

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).
See section 4 “First aid measures”.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Flam. Liq. 3; H226, Flammable liquid and vapour.

Eye Irrit. 2; H319, Causes serious eye irritation.

2.2. Label elements

Hazard pictogram(s)

Signal word

Warning

Hazard statement(s)

Flammable liquid and vapour. (H226)
Causes serious eye irritation. (H319)

Safety statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)

Keep out of reach of children. (P102)

Prevention

Wear eye protection/protective gloves. (P280)

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)

Storage

Store in a well-ventilated place. Keep cool. (P403+P235)

Disposal

Dispose of contents/container to an approved waste disposal plant. (P501)

Hazardous substances

propan-2-ol

2.3. Other hazards

Additional labelling

Not applicable

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
propan-2-ol	CAS No.: 67-63-0 EC No.: 200-661-7 REACH: Index No.: 603-117-00-0	10-15%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
2-butoxyethanol	CAS No.: 111-76-2 EC No.: 203-905-0 REACH: Index No.: 603-014-00-0	5-10%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332	[1]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit

Labelling of contents according to Detergents Regulation (EC) No 648/2004

< 5%

· Anionic surfactants

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Upon irritation: rinse with water. In the event of continued irritation, seek medical assistance.

Eye contact

Upon irritation of the eye: Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30°C) for at least 5 minutes and continue until irritation stops. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:
Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.
If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:
Carbon oxides (CO / CO2).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it.
Ensure sufficient ventilation.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.
Use sand, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.
To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 on “Disposal considerations” in regard of handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ground and bond container and receiving equipment.
Use explosion-proof [electrical / lighting / ventilating] equipment.
Use non-sparking tools.
Take action to prevent static discharges.
The product should be tested for peroxides before distillation or evaporation and tested for peroxide formation or discarded after 1 year.
Peroxide formation may be present anywhere in the container, including the sides, bottom, exterior and threaded cap. Peroxide formation in ppm concentrations may not be visually observable and must be identified through the use of appropriate testing procedures. If any of the following conditions exist, the material may be explosively unstable and will require stabilization prior to use:
1. Material appears to be degraded and or contaminated.
2. Material appears to be discolored.
3. Deterioration or distortion of storage container.
4. Thermal shock (sunlight).
5. Age of material exceeds recommended storage time.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.
Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
Take action to prevent static discharges.
Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

Dry, cool and well ventilated

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

—
propan-2-ol
Long term exposure limit (8 hours) (ppm): 400
Long term exposure limit (8 hours) (mg/m³): 999
Short term exposure limit (15 minutes) (ppm): 500
Short term exposure limit (15 minutes) (mg/m³): 1250

—
2-butoxyethanol
Long term exposure limit (8 hours) (ppm): 25
Long term exposure limit (8 hours) (mg/m³): 123
Short term exposure limit (15 minutes) (ppm): 50
Short term exposure limit (15 minutes) (mg/m³): 246
Annotations:
BMVG = Biological Monitoring Guidance Value exists
Sk = Can be absorbed through the skin and lead to systemic toxicity.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

Product/substance	propan-2-ol
DNEL	319 mg/kg bw/day
Route of exposure	Dermal
Duration	Long term – Systemic effects - General population

Product/substance	propan-2-ol
DNEL	89 mg/m³
Route of exposure	Inhalation
Duration	Long term – Systemic effects - General population

Product/substance	propan-2-ol
DNEL	26 mg/kg bw/day
Route of exposure	Oral
Duration	Long term – Systemic effects - General population

Product/substance	propan-2-ol
DNEL	888 mg/kg bw/day
Route of exposure	Dermal
Duration	Long term – Systemic effects - Workers

Product/substance	propan-2-ol
DNEL	500 mg/m³
Route of exposure	Inhalation
Duration	Long term – Systemic effects - Workers

Product/substance	2-butoxyethanol
DNEL	98 mg/m³
Route of exposure	Inhalation
Duration	Long term – Systemic effects - Workers

Product/substance	2-butoxyethanol
DNEL	1 091 mg/m³
Route of exposure	Inhalation
Duration	Short term – Systemic effects - Workers

Product/substance	2-butoxyethanol
DNEL	246 mg/m³
Route of exposure	Inhalation
Duration	Short term – Local effects - Workers

Product/substance	2-butoxyethanol
DNEL	59 mg/m³
Route of exposure	Inhalation
Duration	Long term – Systemic effects - General population

Product/substance	2-butoxyethanol
DNEL	426 mg/m³
Route of exposure	Inhalation
Duration	Short term – Systemic effects - General population

Product/substance	2-butoxyethanol
DNEL	147 mg/m³
Route of exposure	Inhalation
Duration	Short term – Local effects - General population

Product/substance	2-butoxyethanol
DNEL	6.3 mg/kg bw/day
Route of exposure	Oral
Duration	Long term – Systemic effects - General population

Product/substance	2-butoxyethanol
DNEL	26.7 mg/kg bw/day
Route of exposure	Oral
Duration	Short term – Systemic effects - General population

PNEC

Product/substance	propan-2-ol
PNEC	552 mg/kg
Route of exposure	Marine water sediment
Duration of Exposure	

Product/substance	propan-2-ol
PNEC	140.9 mg/L
Route of exposure	Freshwater
Duration of Exposure	

Product/substance	propan-2-ol
PNEC	28 mg/kg
Route of exposure	Soil
Duration of Exposure	

Product/substance	propan-2-ol
PNEC	140.9 mg/L
Route of exposure	Marine water
Duration of Exposure	

Product/substance	propan-2-ol
PNEC	140.9 mg/L
Route of exposure	Intermittent release
Duration of Exposure	

Product/substance	propan-2-ol
PNEC	2251 mg/L
Route of exposure	Sewage treatment plant
Duration of Exposure	

Product/substance	propan-2-ol
PNEC	552 mg/kg
Route of exposure	Freshwater sediment

Duration of Exposure	

Product/substance	2-butoxyethanol
PNEC	8.8 mg/L
Route of exposure	Freshwater
Duration of Exposure	

Product/substance	2-butoxyethanol
PNEC	0.88 mg/L
Route of exposure	Marine water
Duration of Exposure	

Product/substance	2-butoxyethanol
PNEC	463 mg/L
Route of exposure	Sewage treatment plant
Duration of Exposure	

Product/substance	2-butoxyethanol
PNEC	34.6 mg/kg
Route of exposure	Freshwater sediment
Duration of Exposure	

Product/substance	2-butoxyethanol
PNEC	3.46 mg/kg
Route of exposure	Marine water sediment
Duration of Exposure	

Product/substance	2-butoxyethanol
PNEC	2.33 mg/kg
Route of exposure	Soil
Duration of Exposure	

Product/substance	2-butoxyethanol
PNEC	26.4 mg/L
Route of exposure	Intermittent release
Duration of Exposure	

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

Respiratory Equipment

No specific requirements

Skin protection

No specific requirements

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	-	> 480	EN374-2, EN374-3, EN388	

Eye protection

Type	Standards	
Safety glasses with side shields.	EN166	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Blue

Odour / Odour threshold

Characteristic

pH

10.5

Density (g/cm³)

0.975

Kinematic viscosity

Testing not relevant or not possible due to nature of the product.

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

Testing not relevant or not possible due to nature of the product.

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

Testing not relevant or not possible due to nature of the product.

Vapour pressure

Testing not relevant or not possible due to nature of the product.

Relative vapour density

Testing not relevant or not possible due to nature of the product.

Decomposition temperature (°C)
Testing not relevant or not possible due to nature of the product.

Data on fire and explosion hazards

Flash point (°C)
35

Ignition (°C)
Testing not relevant or not possible due to nature of the product.

Auto flammability (°C)
Testing not relevant or not possible due to nature of the product.

Lower and upper explosion limit (% v/v)
Testing not relevant or not possible due to nature of the product.

Solubility

Solubility in water
Soluble

n-octanol/water coefficient
Testing not relevant or not possible due to nature of the product.

Solubility in fat (g/L)
Testing not relevant or not possible due to nature of the product.

9.2. Other information

Other physical and chemical parameters
No data available

SECTION 10: Stability and reactivity

10.1. Reactivity
No data available

10.2. Chemical stability
The product is stable under the conditions, noted in section 7 “Handling and storage”.

10.3. Possibility of hazardous reactions
No special

10.4. Conditions to avoid
Avoid static electricity.

10.5. Incompatible materials
Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products
The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	propan-2-ol
Test method	OECD 401
Species	Rat
Route of exposure	Oral
Test	LD50
Result	5840 mg/kg
Other information	

Product/substance	propan-2-ol
Test method	OECD 403
Species	Rat
Route of exposure	Inhalation
Test	LC50

Result	>25 mg/L
Other information	

Product/substance	propan-2-ol
Test method	OECD 402
Species	Rabbit
Route of exposure	Dermal
Test	LD50
Result	13900 mg/kg
Other information	

Product/substance	2-butoxyethanol
Test method	
Species	Guinea pig
Route of exposure	Oral
Test	LD50
Result	1414 mg/kg
Other information	

Product/substance	2-butoxyethanol
Test method	
Species	Guinea pig, female
Route of exposure	Inhalation
Test	LC0
Result	>3.1 mg/L
Other information	

Product/substance	2-butoxyethanol
Test method	
Species	Rat
Route of exposure	Oral
Test	LD50
Result	1300 mg/kg
Other information	

Product/substance	2-butoxyethanol
Test method	
Species	Guinea pig
Route of exposure	Dermal
Test	LD0
Result	>2000 mg/kg
Other information	

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity
Based on available data, the classification criteria are not met.

Carcinogenicity
Based on available data, the classification criteria are not met.

Reproductive toxicity
Based on available data, the classification criteria are not met.

STOT-single exposure
Based on available data, the classification criteria are not met.

STOT-repeated exposure
Based on available data, the classification criteria are not met.

Aspiration hazard
Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects
This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Endocrine disrupting properties
No special

Other information
propan-2-ol has been classified by IARC as a group 3 carcinogen.
2-butoxyethanol has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance	propan-2-ol
Test method	
Species	Fish
Compartment	
Duration	96 hours
Test	LC50
Result	>100 mg/L
Other information	

Product/substance	propan-2-ol
Test method	
Species	Algae
Compartment	
Duration	8 d
Test	LOEC
Result	1000 mg/L
Other information	

Product/substance	propan-2-ol
Test method	
Species	Daphnia, Daphnia magna
Compartment	
Duration	48 hours
Test	LC50
Result	>100 mg/L
Other information	

Product/substance	propan-2-ol

Test method	
Species	Algae
Compartment	
Duration	72 hours
Test	EC50
Result	>100 mg/L
Other information	

Product/substance	2-butoxyethanol
Test method	
Species	Algae, Pseudokirchneriella subcapitata
Compartment	
Duration	72 hours
Test	EC50
Result	1840 mg/L
Other information	

Product/substance	2-butoxyethanol
Test method	
Species	Fish, Oncorhynchus mykiss
Compartment	
Duration	96 hours
Test	LC50
Result	1474 mg/L
Other information	

Product/substance	2-butoxyethanol
Test method	
Species	Daphnia, Daphnia magna
Compartment	
Duration	48 hours
Test	EC50
Result	1550 mg/L
Other information	

Product/substance	2-butoxyethanol
Test method	
Species	Fish, Danio rerio
Compartment	
Duration	21 days
Test	NOEC
Result	100 mg/L
Other information	

Product/substance	2-butoxyethanol
Test method	
Species	Daphnia, Daphnia magna
Compartment	
Duration	21 days
Test	NOEC
Result	100 mg/L

Other information

12.2. Persistence and degradability

Product/substance	propan-2-ol
Biodegradable	Yes
Test method	
Result	

Product/substance	2-butoxyethanol
Biodegradable	Yes
Test method	OECD 301 B
Result	90,4%

12.3. Bioaccumulative potential

Product/substance	propan-2-ol
Test method	
Potential bioaccumulation	No
LogPow	0.0500
BCF	No data available
Other information	

Product/substance	2-butoxyethanol
Test method	
Potential bioaccumulation	No
LogPow	0.8100
BCF	No data available
Other information	

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

No special

12.7. Other adverse effects

No special

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.
To the extent the material has not been subject to regular tests of peroxide formation the waste shall be treated as explosive waste.
HP 3 - Flammable
Dispose of contents/container to an approved waste disposal plant.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

07 06 04* Other organic solvents, washing liquids and mother liquors

Specific labelling

Not applicable

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information
ADR	UN1993	FLAMMABLE LIQUID, N.O.S. (propan-2-ol)	Class: 3 Labels: 3 Classification code: F1 	III	No	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1993	FLAMMABLE LIQUID, N.O.S. (propan-2-ol)	Class: 3 Labels: 3 Classification code: F1 	III	No	Limited quantities: 5 L EmS: F-E S-E See below for additional information.
IATA	UN1993	FLAMMABLE LIQUID, N.O.S. (propan-2-ol)	Class: 3 Labels: 3 Classification code: F1 	III	No	See below for additional information.

* Packing group

** Environmental hazards

Additional information

IMDG / See the Dangerous Goods List, section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

14.6. Special precautions for user

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements

SEVESO - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

Additional information

Not applicable

Sources

The Health and Safety at Work etc. Act 1974 Regulations 2013.
Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents.
Control of Major Accident Hazards (COMAH) Regulations 2015.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste.
CLP Regulation (EC) No 1272/2008, as retained and amended in UK law.
EC-Regulation 1907/2006 (REACH), as amended by UK REACH Regulations SI 2019/758

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.
H302, Harmful if swallowed.
H315, Causes skin irritation.
H319, Causes serious eye irritation.
H332, Harmful if inhaled.
H336, May cause drowsiness or dizziness.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).

The classification of the substance/mixture in regard of physical hazards has been based on experimental data.

The safety data sheet is validated by

Åsa Möller

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en