

# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Trade name**

Glue Remover

**Product no.**

-

**REACH registration number**

Not applicable

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Glue remover

**Uses advised against**

-

The full text of any mentioned and identified use categories are given in section 16

### 1.3. Details of the supplier of the safety data sheet

**Company and address**

**Blue & Green AB**  
**Stenorsvägen 52**  
**261 44 Landskrona**  
**Sweden**  
**Tfn: +46 418 399000**  
**Fax: +46 418 13199**  
**www.blueandgreen.se**

**E-mail**

info@blueandgreen.se

**SDS date**

2020-09-17

**SDS Version**

1.0

### 1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Eye Irrit. 2; H319

See full text of H-phrases in section 2.2.

### 2.2. Label elements

**Hazard pictogram(s)**



**Signal word**

Warning

**Hazard statement(s)**

Causes serious eye irritation. (H319)

**Precautionary statements**

**General**

If medical advice is needed, have product container or label at hand. (P101).  
Keep out of reach of children. (P102).

According to EC-Regulation 2015/830

<b>Prevention</b>	Wash hands/exposed skin thoroughly after handling. (P264). Wear eye protection/gloves. (P280).
<b>Response</b>	If eye irritation persists: Get medical advice/attention. (P337+P313). IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338).
<b>Storage</b>	-
<b>Disposal</b>	-

**Identity of the substances primarily responsible for the major health hazards**

Not applicable

**Additional labelling**

Not applicable

**Unique formula identifier (UFI)**

-

**2.3. Other hazards**

This product contains an organic solvent. Repeated or prolonged exposure to organic solvents may result in adverse effects to the nervous system and internal organs such as liver and kidneys.

**Additional warnings**

Not applicable

**VOC (volatile organic compound)**

Not applicable

**SECTION 3: Composition/information on ingredients**

**3.1/3.2. Substances/Mixtures**

NAME: (2-methoxymethylethoxy)propanol  
IDENTIFICATION NOS.: CAS-no: 34590-94-8 EC-no: 252-104-2 REACH-no: 01-2119450011-60  
CONTENT: 40-60%  
CLP CLASSIFICATION:  
NOTE: O L

NAME: 1-(1-methyl-2-propoxyethoxy)propan-2-ol  
IDENTIFICATION NOS.: CAS-no: 29911-27-1 EC-no: 249-949-4 REACH-no: 01-2119908226-42  
CONTENT: 15 - <25%  
CLP CLASSIFICATION: NA

NAME: 2-(2-butoxyethoxy)ethanol  
IDENTIFICATION NOS.: CAS-no: 112-34-5 EC-no: 203-961-6 REACH-no: 01-2119475104-44 Index-no: 603-096-00-8  
CONTENT: 15 - <25%  
CLP CLASSIFICATION: Eye Irrit. 2  
H319  
NOTE: L

(\*) O = Organic solvent L = European occupational exposure limit. See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

**Other information**

Eye Cat. 2 Sum = Sum(Ci/S(G)CLi) = 1.6 - 2.4

Detergent:

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service: Dial 0344 892 0111 (24 h service). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

**Inhalation**

Bring the person into fresh air and stay with him/her.

**Skin contact**

Immediately remove contaminated clothing and shoes. Ensure that skin, which has been exposed to the material, is washed thoroughly with soap and water.

According to EC-Regulation 2015/830

#### Eye contact

Remove contact lenses. Flush eyes with plenty of water or salt water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing.

#### Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

#### Burns

Not applicable

#### 4.2. Most important symptoms and effects, both acute and delayed

This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: headache, dizziness, ringing in ears, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned: Get immediate medical advice/attention.

#### Information to medic

Bring this safety data sheet.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist.

#### 5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

No specific requirements.

#### 6.2. Environmental precautions

No specific requirements.

#### 6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

#### 6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Smoking, storage of tobacco, consumption and storage of food or liquids are not allowed in the workrooms. See section on 'Exposure controls/personal protection' for information on personal protection.

#### 7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### Storage temperature

Room temperature 18 to 23°C

#### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

According to EC-Regulation 2015/830

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### OEL

2-(2-butoxyethoxy)ethanol

Long-term exposure limit (8-hour TWA reference period): 10 ppm | 67,5 mg/m<sup>3</sup>

Short-term exposure limit (15-minute reference period): 15 ppm | 101.2 mg/m<sup>3</sup>

(2-methoxymethylethoxy)propanol

Long-term exposure limit (8-hour TWA reference period): 50 ppm | 308 mg/m<sup>3</sup>

Short-term exposure limit (15-minute reference period): - ppm | - mg/m<sup>3</sup>

Comments: Sk (Sk = Can be absorbed through skin. )

#### DNEL / PNEC

DNEL (2-(2-butoxyethoxy)ethanol): 83 mg/kg

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (2-(2-butoxyethoxy)ethanol): 67.5 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (2-(2-butoxyethoxy)ethanol): 67.5 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - Workers

DNEL (2-(2-butoxyethoxy)ethanol): 5 mg/kg bw/d

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-(2-butoxyethoxy)ethanol): 50 mg/kg bw/d

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-(2-butoxyethoxy)ethanol): 40.5 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - General population

DNEL (2-(2-butoxyethoxy)ethanol): 101.2 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Short term – Local effects - Workers

DNEL (2-(2-butoxyethoxy)ethanol): 40.5 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-(2-butoxyethoxy)ethanol): 60.7 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Short term – Local effects - General population

DNEL ((2-methoxymethylethoxy)propanol): 283 mg/kg bw/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL ((2-methoxymethylethoxy)propanol): 308 mg/kg

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL ((2-methoxymethylethoxy)propanol): 121 mg/kg bw/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL ((2-methoxymethylethoxy)propanol): 37.2 mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL ((2-methoxymethylethoxy)propanol): 36 mg/kg bw/day

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

DNEL (1-(1-methyl-2-propoxyethoxy)propan-2-ol): 60mg/kg

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

According to EC-Regulation 2015/830

DNEL (1-(1-methyl-2-propoxyethoxy)propan-2-ol): 84mg/m<sup>3</sup>  
 Exposure: Inhalation  
 Duration of Exposure: Long term – Systemic effects - Workers

DNEL (1-(1-methyl-2-propoxyethoxy)propan-2-ol): 30mg/kg  
 Exposure: Dermal  
 Duration of Exposure: Long term – Systemic effects - General population

DNEL (1-(1-methyl-2-propoxyethoxy)propan-2-ol): 21mg/m<sup>3</sup>  
 Exposure: Inhalation  
 Duration of Exposure: Long term – Systemic effects - General population

DNEL (1-(1-methyl-2-propoxyethoxy)propan-2-ol): 6mg/kg  
 Exposure: Oral  
 Duration of Exposure: Long term – Systemic effects - General population

PNEC (2-(2-butoxyethoxy)ethanol): 200 mg/l  
 Exposure: Sewage Treatment Plant

PNEC (2-(2-butoxyethoxy)ethanol): 0.44 mg/kg dw  
 Exposure: Marine water sediment

PNEC (2-(2-butoxyethoxy)ethanol): 4.4 mg/kg dw  
 Exposure: Freshwater sediment

PNEC (2-(2-butoxyethoxy)ethanol): 1 mg/l  
 Exposure: Freshwater

PNEC (2-(2-butoxyethoxy)ethanol): 0.1 mg/l  
 Exposure: Marine water

PNEC (2-(2-butoxyethoxy)ethanol): 3.9 mg/l  
 Exposure: Intermittent release

PNEC (2-(2-butoxyethoxy)ethanol): 0.32 mg/kg dw  
 Exposure: Soil

PNEC ((2-methoxymethylethoxy)propanol): 19 mg/l  
 Exposure: Freshwater

PNEC ((2-methoxymethylethoxy)propanol): 1.9 mg/l  
 Exposure: Marine water

PNEC ((2-methoxymethylethoxy)propanol): 190 mg/l  
 Exposure: Intermittent release

PNEC ((2-methoxymethylethoxy)propanol): 70.2 mg/kg/dwt  
 Exposure: Freshwater sediment

PNEC ((2-methoxymethylethoxy)propanol): 7.02 mg/kg/dwt  
 Exposure: Marine water sediment

PNEC ((2-methoxymethylethoxy)propanol): 2.74 mg/kg  
 Exposure: Soil

PNEC ((2-methoxymethylethoxy)propanol): 4168 mg/l  
 Exposure: Sewage Treatment Plant

## 8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

### General recommendations

Observe general occupational hygiene standards.

### Exposure scenarios

There is no appendix to this safety data sheet.

### Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

### Appropriate technical measures

Ensure emergency eyewash and -showers are clearly marked.

### Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be

According to EC-Regulation 2015/830

washed thoroughly. Always wash hands, forearms and face.

**Measures to avoid environmental exposure**

No specific requirements.

**Individual protection measures, such as personal protective equipment**



**Generally**

Use only CE marked protective equipment.

**Respiratory Equipment**

NA

**Skin protection**

Wear appropriate protection clothing, e.g. coveralls in polypropylene approved type 6 and Category III.

**Hand protection**

Butyl rubber

Breakthrough time: > 480 minutes (Class 6)

**Eye protection**

Wear safety glasses with side shields.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Form	Liquid
Colour	Colourless
Odour	Characteristic
Odour threshold (ppm)	No data available.
pH	No data available.
Viscosity (40°C)	No data available.
Density (g/cm <sup>3</sup> )	0.94

**Phase changes**

Melting point (°C)	No data available.
Boiling point (°C)	No data available.
Vapour pressure	No data available.
Decomposition temperature (°C)	No data available.
Evaporation rate (n-butylacetate = 100)	No data available.

**Data on fire and explosion hazards**

Flash point (°C)	82
Ignition (°C)	No data available.
Auto flammability (°C)	No data available.
Explosion limits (% v/v)	No data available.
Explosive properties	No data available.

**Solubility**

Solubility in water	Insoluble
n-octanol/water coefficient	No data available.

**9.2. Other information**

Solubility in fat (g/L)	No data available.
-------------------------	--------------------

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No data available

**10.2. Chemical stability**

The product is stable under the conditions, noted in the section "Handling and storage".

**10.3. Possibility of hazardous reactions**

Nothing special

**10.4. Conditions to avoid**

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

According to EC-Regulation 2015/830

**10.5. Incompatible materials**

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

**10.6. Hazardous decomposition products**

The product is not degraded when used as specified in section 1.

**SECTION 11: Toxicological information**

**11.1. Information on toxicological effects**

**Acute toxicity**

Substance: 2-(2-butoxyethoxy)ethanol

Species: Rat

Test: LD50

Route of exposure: Oral

Result: >2000 mg/kg

Substance: 2-(2-butoxyethoxy)ethanol

Species: Rabbit

Test: LD50

Route of exposure: Dermal

Result: 2764 mg/kg

Substance: 2-(2-butoxyethoxy)ethanol

Species: Rat

Test: LC50

Route of exposure: Inhalation

Result: >29 ppm 2h

Substance: 2-(2-butoxyethoxy)ethanol

Species: Mouse

Test: LD50

Route of exposure: Oral

Result: 2410 mg/kg

Substance: 1-(1-methyl-2-propoxyethoxy)propan-2-ol

Species: Rat

Test: LD50

Route of exposure: Oral

Result: 2000mg/kg

Substance: 1-(1-methyl-2-propoxyethoxy)propan-2-ol

Species: Rat

Test: LD50

Route of exposure: Dermal

Result: 2000mg/kg

Substance: (2-methoxymethylethoxy)propanol

Species: Rat

Test: LD50

Route of exposure: Oral

Result: 5000 mg/kg

Substance: (2-methoxymethylethoxy)propanol

Species: Rabbit

Test: LD50

Route of exposure: Dermal

Result: 9510 mg/kg

Substance: (2-methoxymethylethoxy)propanol

Species: Rat

Test: LC50

Route of exposure: Inhalation

Result: 3.35 mg/l 7h ånga

**Skin corrosion/irritation**

Data on substance: 2-(2-butoxyethoxy)ethanol

Test: OECD Guideline 404

Organism: Rabbit

Result: not irritating

**Serious eye damage/irritation**

Causes serious eye irritation.

Data on substance: 2-(2-butoxyethoxy)ethanol

Test: OECD Guideline 404

According to EC-Regulation 2015/830

Organism: Rabbit

Result: irritating

**Respiratory or skin sensitisation**

Data on substance: 2-(2-butoxyethoxy)ethanol

Test: OECD Guideline 406

Organism: Guinea pig

Result: Negative

**Germ cell mutagenicity**

No data available.

**Carcinogenicity**

No data available.

**Reproductive toxicity**

No data available.

**STOT-single exposure**

No data available.

**STOT-repeated exposure**

No data available.

**Aspiration hazard**

No data available.

**Long term effects**

This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: headache, dizziness, ringing in ears, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

**SECTION 12: Ecological information**

**12.1. Toxicity**

Substance: 2-(2-butoxyethoxy)ethanol

Species: Fish

Test: LC50

Duration: 96h

Result: >100 mg/l

Substance: 2-(2-butoxyethoxy)ethanol

Species: Algae

Test: EC50

Duration: 96h

Result: >100 mg/l

Substance: 2-(2-butoxyethoxy)ethanol

Species: Daphnia

Test: EC50

Duration: 48h

Result: >100 mg/l

Substance: 1-(1-methyl-2-propoxyethoxy)propan-2-ol

Species: Fish

Test: LC50

Duration: 96h

Result: >100mg/l

Substance: 1-(1-methyl-2-propoxyethoxy)propan-2-ol

Species: Daphnia

Test: EC50

Duration: 48h

Result: >100mg/l

Substance: 1-(1-methyl-2-propoxyethoxy)propan-2-ol

Species: Algae

Test: EC50

Duration:

Result: >1000mg/l

Substance: (2-methoxymethylethoxy)propanol

Species: Fish

Test: LC50

Duration: 96h

Result: >1000 mg/l

Substance: (2-methoxymethylethoxy)propanol

Species: Daphnia

Test: EC50



According to EC-Regulation 2015/830

Duration: 48h  
Result: 1919 mg/l

Substance: (2-methoxymethylethoxy)propanol  
Species: Daphnia  
Test: NOEC  
Duration: 22d  
Result: 0.5 mg/l

Substance: (2-methoxymethylethoxy)propanol  
Species: Algae  
Test: EC50  
Duration: 72h  
Result: 969 mg/l

### 12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
2-(2-butoxyethoxy)ethanol	Yes	Modified OECD Screening Test	100%
1-(1-methyl-2-propoxyethoxy)pr...	Yes	DOC Die-Away Test	92%
(2-methoxymethylethoxy)propano...	Yes	DOC Die-Away Test	75%

### 12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BCF
2-(2-butoxyethoxy)ethanol	No	1	No data available
1-(1-methyl-2-propoxyethoxy)pr...	No	0.88	No data available
(2-methoxymethylethoxy)propano...	No	0.006	No data available

### 12.4. Mobility in soil

2-(2-butoxyethoxy)ethanol: Log Koc= 0.8703, Calculated from LogPow (High mobility potential.).  
1-(1-methyl-2-propoxyethoxy)pr...: Log Koc= 2.8 (Moderate mobility potential.).  
(2-methoxymethylethoxy)propano...: Log Koc= 0.28 (High mobility potential.).

### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

### 12.6. Other adverse effects

Nothing special

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

#### Waste

EWC code

-

#### Specific labelling

Not applicable

#### Contaminated packing

Contaminated packaging must be disposed of similarly to the product.

## SECTION 14: Transport information

### 14.1 – 14.4

Not dangerous goods according to ADR, IATA and IMDG.

#### ADR/RID

14.1. UN number	-
14.2. UN proper shipping name	-
14.3. Transport hazard class(es)	-
14.4. Packing group	-
Notes	-
Tunnel restriction code	-

#### IMDG

UN-no.	-
Proper Shipping Name	-
Class	-
PG*	-
EmS	-
MP**	-
Hazardous constituent	-

#### IATA/ICAO

According to EC-Regulation 2015/830

UN-no. -  
 Proper Shipping Name -  
 Class -  
 PG\* -

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

-

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No data available

(\*) Packing group

(\*\*) Marine pollutant

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Restrictions for application**

People under the age of 18 shall not be exposed to this product cf. Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

**Demands for specific education**

-

**Additional information**

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

**Seveso**

-

**Biocidal reg. no.**

Not applicable

**Sources**

Council Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding.

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.

Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).

Regulation (EC) 1907/2006 (REACH).

**15.2. Chemical safety assessment**

No

**SECTION 16: Other information**

**Full text of H-phrases as mentioned in section 3**

H319 - Causes serious eye irritation.

**The full text of identified uses as mentioned in section 1**

-

**Additional label elements**

Not applicable

**Other**

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on:

The classification of the mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

According to EC-Regulation 2015/830

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

**The safety data sheet is validated by**

David Löwenstein

**Date of last essential change  
(First cipher in SDS version)**

-

**Date of last minor change  
(Last cipher in SDS version)**

-