

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Graffiti Remover Train N

Product no.

-

REACH registration number

Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Graffiti Removal

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

Blue & Green AB
Stenorsvägen 52
261 44 Landskrona
Sweden
Tfn: +46 418 399000
Fax: +46 418 13199
www.blueandgreen.se

E-mail

info@blueandgreen.se

SDS date

2020-09-11

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Aquatic Chronic 3; H412
 See full text of H-phrases in section 2.2.

2.2. Label elements

Hazard pictogram(s)

Not applicable

Signal word

-

Hazard statement(s)

Harmful to aquatic life with long lasting effects. (H412)

Precautionary statements

| | |
|------------|---|
| General | If medical advice is needed, have product container or label at hand. (P101). |
| Prevention | Avoid release to the environment. (P273). |
| Response | - |
| Storage | - |
| Disposal | Dispose of contents/container to an approved waste disposal plant. (P501). |

Identity of the substances primarily responsible for the major health hazards

Not applicable

According to EC-Regulation 2015/830

Additional labelling

Not applicable

Unique formula identifier (UFI)

TCQ6-13UF-R10K-9USH

2.3. Other hazards

Not applicable

Additional warnings

Not applicable

VOC (volatile organic compound)

Not applicable

SECTION 3: Composition/information on ingredients

3.1/3.2. Substances/Mixtures

| | |
|----------------------|--|
| NAME: | dimethyl glutarate |
| IDENTIFICATION NOS.: | CAS-no: 1119-40-0 EC-no: 214-277-2 REACH-no: 01-2119900156-49 |
| CONTENT: | 25-40% |
| CLP CLASSIFICATION: | NA |
| NAME: | (2-methoxymethylethoxy)propanol |
| IDENTIFICATION NOS.: | CAS-no: 34590-94-8 EC-no: 252-104-2 REACH-no: 01-2119450011-60 |
| CONTENT: | 15 - <25% |
| CLP CLASSIFICATION: | |
| NOTE: | O L |
| NAME: | Dipropylene glycol dimethyl ether |
| IDENTIFICATION NOS.: | CAS-no: 111109-77-4 EC-no: 404-640-5 REACH-no: 01-0000015420-83 |
| CONTENT: | 15 - <25% |
| CLP CLASSIFICATION: | NA |
| NAME: | dimethyl succinate |
| IDENTIFICATION NOS.: | CAS-no: 106-65-0 EC-no: 203-419-9 REACH-no: 01-2119486681-29 |
| CONTENT: | 10 - <15% |
| CLP CLASSIFICATION: | NA |
| NAME: | 2-(2-butoxyethoxy)ethanol |
| IDENTIFICATION NOS.: | CAS-no: 112-34-5 EC-no: 203-961-6 REACH-no: 01-2119475104-44 Index-no: 603-096-00-8 |
| CONTENT: | 5 - <10% |
| CLP CLASSIFICATION: | Eye Irrit. 2 H319 |
| NOTE: | L |
| NAME: | dimethyl adipate |
| IDENTIFICATION NOS.: | CAS-no: 627-93-0 EC-no: 211-020-6 REACH-no: 01-2119911093-50 |
| CONTENT: | 2.5 - <5% |
| CLP CLASSIFICATION: | NA |
| NAME: | Fatty acids, tall-oil |
| IDENTIFICATION NOS.: | CAS-no: 61790-12-3 EC-no: 263-107-3 |
| CONTENT: | 1 - <2.5% |
| CLP CLASSIFICATION: | NA |
| NAME: | Hydroxypropylmethylcellulosa |
| IDENTIFICATION NOS.: | CAS-no: 9004-65-3 |
| CONTENT: | 1 - <2.5% |
| CLP CLASSIFICATION: | NA |
| NAME: | Oleylamine ethoxylate |
| IDENTIFICATION NOS.: | CAS-no: 26635-93-8 EC-no: 500-048-7 REACH-no: 01-2120785735-39 |
| CONTENT: | 0.25 - <1% |
| CLP CLASSIFICATION: | Acute Tox. 4, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1 H302, H318, H400, H410 (M-acute = 1) (M-chronic = 1) |

(*) O = Organic solvent L = European occupational exposure limit. See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

ATEmix(oral) > 2000
 Eye Cat. 2 Sum = Sum(Ci/S(G)CLi) = 0.76 - < 1
 N chronic (CAT 3) Sum = Sum(Ci/(M(chronic)ⁱ*25)*0.1*10[^]CATi) = 1.6 - 2.4

According to EC-Regulation 2015/830

$N_{acute} (CAT 1)_{Sum} = \sum(C_i/M_{(acute)})^{*25} = 0.016 - 0.024$

Detergent:

< 5%: AMPHOTERIC SURFACTANTS, NON-IONIC SURFACTANTS, SORBITAN TRIOLEATE

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service: Dial 0344 892 0111 (24 h service). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Bring the person into fresh air and stay with him/her.

Skin contact

Immediately remove contaminated clothing and shoes. Ensure that skin, which has been exposed to the material, is washed thoroughly with soap and water.

Eye contact

Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30°C) for at least 5 minutes and continue until irritation stops. Make sure to flush under the upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Not applicable

4.2. Most important symptoms and effects, both acute and delayed

Nothing special

4.3. Indication of any immediate medical attention and special treatment needed

Nothing special

Information to medic

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No specific requirements.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities. It is recommended to install waste collection trays to prevent emissions to the waste water system and surrounding environment.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

6.4. Reference to other sections

According to EC-Regulation 2015/830

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, storage of tobacco, consumption and storage of food or liquids are not allowed in the workrooms. It is recommended to install waste collection trays to prevent emissions to the waste water system and surrounding environment. See section on 'Exposure controls/personal protection' for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Storage temperature

No data available.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL

2-(2-butoxyethoxy)ethanol

Long-term exposure limit (8-hour TWA reference period): 10 ppm | 67,5 mg/m³

Short-term exposure limit (15-minute reference period): 15 ppm | 101.2 mg/m³

(2-methoxymethylethoxy)propanol

Long-term exposure limit (8-hour TWA reference period): 50 ppm | 308 mg/m³

Short-term exposure limit (15-minute reference period): - ppm | - mg/m³

Comments: Sk (Sk = Can be absorbed through skin.)

DNEL / PNEC

DNEL (dimethyl succinate): 1,1mg/m³

Exposure: Inhalation

Duration of Exposure: Short term – Local effects - Workers

DNEL (dimethyl succinate): 6.8mg/kg/d

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (dimethyl succinate): 33,5mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (dimethyl succinate): 1,1mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - Workers

DNEL (dimethyl succinate): 12,6mg/kg

Exposure: Dermal

Duration of Exposure: Short term – Systemic effects - Workers

DNEL (dimethyl succinate): 67mg/m³

Exposure: Inhalation

Duration of Exposure: Short term – Systemic effects - Workers

DNEL (dimethyl glutarate): 8,3mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - Workers

DNEL (dimethyl glutarate): 49,8mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - Workers

DNEL (dimethyl glutarate): 5mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - General population

DNEL (dimethyl glutarate): 50mg/m³

Exposure: Inhalation

Duration of Exposure: Short term – Local effects - General population

According to EC-Regulation 2015/830

DNEL (2-(2-butoxyethoxy)ethanol): 20 mg/kg bw/d
Exposure: Dermal
Duration of Exposure: Long term – Systemic effects - Workers

DNEL (2-(2-butoxyethoxy)ethanol): 67.5 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Systemic effects - Workers

DNEL (2-(2-butoxyethoxy)ethanol): 67.5 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Local effects - Workers

DNEL (2-(2-butoxyethoxy)ethanol): 7.5 mg/m³
Exposure: Inhalation
Duration of Exposure: Short term – Local effects - General population

DNEL (2-(2-butoxyethoxy)ethanol): 1.25 mg/kg bw/d
Exposure: Oral
Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-(2-butoxyethoxy)ethanol): 10 mg/kg bw/d
Exposure: Dermal
Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-(2-butoxyethoxy)ethanol): 34 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Local effects - General population

DNEL (2-(2-butoxyethoxy)ethanol): 101.2 mg/m³
Exposure: Inhalation
Duration of Exposure: Short term – Local effects - Workers

DNEL (2-(2-butoxyethoxy)ethanol): 34 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Systemic effects - General population

DNEL (Dipropylene glycol dimethyl ether): 22.1 mg/kg bw/d
Exposure: Dermal
Duration of Exposure: Long term – Systemic effects - Workers

DNEL (Dipropylene glycol dimethyl ether): 133 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Systemic effects - Workers

DNEL (Dipropylene glycol dimethyl ether): 5.26 mg/kg bw/d
Exposure: Dermal
Duration of Exposure: Long term – Systemic effects - General population

DNEL (Dipropylene glycol dimethyl ether): 15.8 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Systemic effects - General population

DNEL (Dipropylene glycol dimethyl ether): 1.67 mg/kg bw/d
Exposure: Oral
Duration of Exposure: Long term – Systemic effects - General population

DNEL ((2-methoxymethylethoxy)propanol): 283 mg/kg bw/day
Exposure: Dermal
Duration of Exposure: Long term – Systemic effects - Workers

DNEL ((2-methoxymethylethoxy)propanol): 308 mg/kg
Exposure: Inhalation
Duration of Exposure: Long term – Systemic effects - Workers

DNEL ((2-methoxymethylethoxy)propanol): 121 mg/kg bw/day
Exposure: Dermal
Duration of Exposure: Long term – Systemic effects - General population

DNEL ((2-methoxymethylethoxy)propanol): 37.2 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Systemic effects - General population

According to EC-Regulation 2015/830

DNEL ((2-methoxymethylethoxy)propanol): 36 mg/kg bw/day
Exposure: Oral
Duration of Exposure: Long term – Systemic effects - General population

PNEC (dimethyl succinate): 0,05mg/l
Exposure: Freshwater

PNEC (dimethyl succinate): 0,005mg/l
Exposure: Marine water

PNEC (dimethyl succinate): 0,5mg/l
Exposure: Intermittent release

PNEC (dimethyl succinate): 10mg/l
Exposure: Sewage Treatment Plant

PNEC (dimethyl succinate): 0,137mg/kg
Exposure: Freshwater sediment

PNEC (dimethyl succinate): 0,014mg/kg
Exposure: Marine water sediment

PNEC (dimethyl adipate): 0,018mg/l
Exposure: Freshwater

PNEC (dimethyl adipate): 0,0018mg/l
Exposure: Marine water

PNEC (dimethyl adipate): 0,18mg/l
Exposure: Intermittent release

PNEC (dimethyl adipate): 0,16mg/kg
Exposure: Freshwater sediment

PNEC (dimethyl adipate): 0,016
Exposure: Marine water sediment

PNEC (dimethyl adipate): 0,09mg/kg
Exposure: Soil

PNEC (dimethyl adipate): 10mg/l
Exposure: Sewage Treatment Plant

PNEC (dimethyl glutarate): 0,018mg/l
Exposure: Freshwater

PNEC (dimethyl glutarate): 0,0018/mg/l
Exposure: Marine water

PNEC (dimethyl glutarate): 0,018/mg/l
Exposure: Intermittent release

PNEC (dimethyl glutarate): 0,16mg/kg
Exposure: Freshwater sediment

PNEC (dimethyl glutarate): 0,016mg/kg
Exposure: Marine water sediment

PNEC (dimethyl glutarate): 0,09mg/kg
Exposure: Soil

PNEC (dimethyl glutarate): 10mg/l
Exposure: Sewage Treatment Plant

PNEC (2-(2-butoxyethoxy)ethanol): 200 mg/l
Exposure: Sewage Treatment Plant

PNEC (2-(2-butoxyethoxy)ethanol): 0.44 mg/kg dw
Exposure: Marine water sediment

According to EC-Regulation 2015/830

PNEC (2-(2-butoxyethoxy)ethanol): 4.4 mg/kg dw
Exposure: Freshwater sediment

PNEC (2-(2-butoxyethoxy)ethanol): 1 mg/l
Exposure: Freshwater

PNEC (2-(2-butoxyethoxy)ethanol): 0.1 mg/l
Exposure: Marine water

PNEC (2-(2-butoxyethoxy)ethanol): 3.9 mg/l
Exposure: Intermittent release

PNEC (2-(2-butoxyethoxy)ethanol): 0.32 mg/kg dw
Exposure: Soil

PNEC (Dipropylene glycol dimethyl ether): 1 ml/l
Exposure: Freshwater
Remarks: sdb Univar

PNEC (Dipropylene glycol dimethyl ether): 0.1 mg/l
Exposure: Marine water

PNEC (Dipropylene glycol dimethyl ether): 10 mg/l
Exposure: Intermittent release

PNEC (Dipropylene glycol dimethyl ether): 0.1 mg/kg dw
Exposure: Soil

PNEC (Dipropylene glycol dimethyl ether): 1.16 mg/kg dw
Exposure: Freshwater sediment

PNEC (Dipropylene glycol dimethyl ether): 1.16 mg/kg dw
Exposure: Marine water sediment

PNEC (Dipropylene glycol dimethyl ether): 10 mg/l
Exposure: Sewage Treatment Plant

PNEC ((2-methoxymethylethoxy)propanol): 19 mg/l
Exposure: Freshwater

PNEC ((2-methoxymethylethoxy)propanol): 1.9 mg/l
Exposure: Marine water

PNEC ((2-methoxymethylethoxy)propanol): 190 mg/l
Exposure: Intermittent release

PNEC ((2-methoxymethylethoxy)propanol): 70.2 mg/kg/dwt
Exposure: Freshwater sediment

PNEC ((2-methoxymethylethoxy)propanol): 7.02 mg/kg/dwt
Exposure: Marine water sediment

PNEC ((2-methoxymethylethoxy)propanol): 2.74 mg/kg
Exposure: Soil

PNEC ((2-methoxymethylethoxy)propanol): 4168 mg/l
Exposure: Sewage Treatment Plant

8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

General recommendations

Observe general occupational hygiene standards.

Exposure scenarios

There is no appendix to this safety data sheet.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be

According to EC-Regulation 2015/830

washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment



Generally

Use only CE marked protective equipment.

Respiratory Equipment

NA

Skin protection

Dedicated work clothing should be worn.

Hand protection

Nitrile rubber

Breakthrough time: > 480 minutes (Class 6)

Eye protection

Wear safety glasses with side shields.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|------------------------------|--------------------|
| Form | Liquid |
| Colour | Brown |
| Odour | None |
| Odour threshold (ppm) | No data available. |
| pH | No data available. |
| Viscosity (40°C) | No data available. |
| Density (g/cm ³) | 0.95 |

Phase changes

| | |
|---|--------------------|
| Melting point (°C) | No data available. |
| Boiling point (°C) | No data available. |
| Vapour pressure | No data available. |
| Decomposition temperature (°C) | No data available. |
| Evaporation rate (n-butylacetate = 100) | No data available. |

Data on fire and explosion hazards

| | |
|--------------------------|--------------------|
| Flash point (°C) | No data available. |
| Ignition (°C) | No data available. |
| Auto flammability (°C) | No data available. |
| Explosion limits (% v/v) | No data available. |
| Explosive properties | No data available. |

Solubility

| | |
|-----------------------------|--------------------|
| Solubility in water | Insoluble |
| n-octanol/water coefficient | No data available. |

9.2. Other information

| | |
|-------------------------|--------------------|
| Solubility in fat (g/L) | No data available. |
|-------------------------|--------------------|

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

10.3. Possibility of hazardous reactions

Nothing special

10.4. Conditions to avoid

Nothing special

According to EC-Regulation 2015/830

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Substance: Oleylamine ethoxylate

Species: Rat

Test: LD50

Route of exposure: Oral

Result: 300-2000 mg/kg

Substance: Hydroxypropylmethylcellulosa

Species: Rat

Test: LD50

Route of exposure: Oral

Result: >2000mg/kg

Substance: dimethyl adipate

Species: Rat

Test: LD50

Route of exposure: Oral

Result: 5000mg/kg

Substance: dimethyl adipate

Species: Rat

Test: LD50

Route of exposure: Dermal

Result: 2000mg/kg

Substance: dimethyl adipate

Species: Rat

Test: LC50

Route of exposure: Inhalation

Result: 11000mg/l

Substance: 2-(2-butoxyethoxy)ethanol

Species: Rat

Test: LD50

Route of exposure: Oral

Result: >2000 mg/kg

Substance: 2-(2-butoxyethoxy)ethanol

Species: Rabbit

Test: LD50

Route of exposure: Dermal

Result: 2764 mg/kg

Substance: 2-(2-butoxyethoxy)ethanol

Species: Rat

Test: LC50

Route of exposure: Inhalation

Result: >29 ppm 2h

Substance: 2-(2-butoxyethoxy)ethanol

Species: Mouse

Test: LD50

Route of exposure: Oral

Result: 2410mg/kg

Substance: dimethyl succinate

Species: Rat

Test: LD50

Route of exposure: Oral

Result: 5000mg/kg

Substance: dimethyl succinate

Species: Rat

Test: LD50

According to EC-Regulation 2015/830

Route of exposure: Dermal
Result: 2000mg/kg

Substance: dimethyl succinate
Species: Rat
Test: LC50
Route of exposure: Inhalation
Result: 11000mg/l

Substance: Dipropylene glycol dimethyl ether
Species: Rat
Test: LD50
Route of exposure: Oral
Result: 3300 mg/kg

Substance: Dipropylene glycol dimethyl ether
Species: Rat
Test: LD50
Route of exposure: Dermal
Result: >2000 mg/kg

Substance: (2-methoxymethylethoxy)propanol
Species: Rat
Test: LD50
Route of exposure: Oral
Result: 5000 mg/kg

Substance: (2-methoxymethylethoxy)propanol
Species: Rabbit
Test: LD50
Route of exposure: Dermal
Result: 9510 mg/kg

Substance: (2-methoxymethylethoxy)propanol
Species: Rat
Test: LC50
Route of exposure: Inhalation
Result: 3.35 mg/l 7h ånga

Skin corrosion/irritation

Data on substance: 2-(2-butoxyethoxy)ethanol
Test: OECD Guideline 404
Organism: Rabbit
Result: Ingen hudirritation

Serious eye damage/irritation

Data on substance: 2-(2-butoxyethoxy)ethanol
Test: OECD Guideline 404
Organism: Rabbit
Result: Ögonirritation

Respiratory or skin sensitisation

Data on substance: 2-(2-butoxyethoxy)ethanol
Test: OECD Guideline 406
Organism: Guinea pig
Result: Negative

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

No data available.

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

Long term effects

Nothing special

SECTION 12: Ecological information

12.1. Toxicity

Substance: Oleylamine ethoxylate
Species: Fish
Test: LC50

According to EC-Regulation 2015/830

Duration: 96 h
Result: 1-10 mg/l

Substance: Oleylamine ethoxylate
Species: Daphnia
Test: EC50
Duration: 48 h
Result: 0.1-1 mg/l

Substance: Oleylamine ethoxylate
Species: Algae
Test: NOEC
Duration: 72 h
Result: 0.01 mg/l

Substance: dimethyl adipate
Species: Fish
Test: LC50
Duration: 96h
Result: 18-24mg/l

Substance: dimethyl adipate
Species: Daphnia
Test: EC50
Duration: 48h
Result: 112-150mg/l

Substance: dimethyl adipate
Species: Algae
Test: EC50
Duration: 72h
Result: >85mg/l

Substance: 2-(2-butoxyethoxy)ethanol
Species: Fish
Test: LC50
Duration: 96h
Result: >100 mg/l

Substance: 2-(2-butoxyethoxy)ethanol
Species: Algae
Test: EC50
Duration: 96h
Result: >100 mg/l

Substance: 2-(2-butoxyethoxy)ethanol
Species: Daphnia
Test: EC50
Duration: 48h
Result: >100 mg/l

Substance: dimethyl succinate
Species: Fish
Test: LC50
Duration: 96h
Result: 12-24mg/l

Substance: dimethyl succinate
Species: Daphnia
Test: EC50
Duration: 48h
Result: 112-150mg/l

Substance: dimethyl succinate
Species: Algae
Test: EC50
Duration: 72h
Result: >85mg/l

Substance: Dipropylene glycol dimethyl ether
Species: Fish
Test: LC50
Duration: 96h

According to EC-Regulation 2015/830

Result: >1000 mg/l

Substance: Dipropylene glycol dimethyl ether
Species: Daphnia
Test: EC50
Duration: 24h
Result: >1000 mg/l

Substance: Dipropylene glycol dimethyl ether
Species: Algae
Test: EC50
Duration: 72h
Result: >1000 mg/l

Substance: (2-methoxymethylethoxy)propanol
Species: Fish
Test: LC50
Duration: 96h
Result: >1000 mg/l

Substance: (2-methoxymethylethoxy)propanol
Species: Daphnia
Test: EC50
Duration: 48h
Result: 1919 mg/l

Substance: (2-methoxymethylethoxy)propanol
Species: Daphnia
Test: NOEC
Duration: 22d
Result: 0.5 mg/l

Substance: (2-methoxymethylethoxy)propanol
Species: Algae
Test: EC50
Duration: 72h
Result: 969 mg/l

12.2. Persistence and degradability

| Substance | Biodegradability | Test | Result |
|-----------------------------------|------------------|--------------------|-------------------|
| Oleylamine ethoxylate | Yes | CO2 Evolution Test | >60% |
| dimethyl adipate | Yes | No data available | No data available |
| 2-(2-butoxyethoxy)ethanol | Yes | Modified OECD | 100% |
| dimethyl succinate | Yes | Screening Test | No data available |
| Dipropylene glycol dimethyl et... | No | No data available | 32% |
| (2-methoxymethylethoxy)propano... | Yes | CO2 Evolution Test | 75% |
| dimethyl glutarate | Yes | DOC Die-Away Test | No data available |
| | | No data available | |

12.3. Bioaccumulative potential

| Substance | Potential bioaccumulation | LogPow | BCF |
|-----------------------------------|---------------------------|--------|-------------------|
| 2-(2-butoxyethoxy)ethanol | No | 1 | No data available |
| Dipropylene glycol dimethyl et... | No | 0.42 | No data available |
| (2-methoxymethylethoxy)propano... | No | 0.006 | No data available |

12.4. Mobility in soil

2-(2-butoxyethoxy)ethanol: Log Koc= 0.8703, Calculated from LogPow (High mobility potential.).
Dipropylene glycol dimethyl et...: Log Koc= 0.410998, Calculated from LogPow (High mobility potential.).
(2-methoxymethylethoxy)propano...: Log Koc= 0.28 (High mobility potential.).

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.
This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

Waste

EWC code

-

According to EC-Regulation 2015/830

Specific labelling

Not applicable

Contaminated packing

Contaminated packaging must be disposed of similarly to the product.

SECTION 14: Transport information

14.1 – 14.4

Not dangerous goods according to ADR, IATA and IMDG.

ADR/RID

- 14.1. UN number -
- 14.2. UN proper shipping name -
- 14.3. Transport hazard class(es) -
- 14.4. Packing group -
- Notes -
- Tunnel restriction code -

IMDG

- UN-no. -
- Proper Shipping Name -
- Class -
- PG* -
- EmS -
- MP** -
- Hazardous constituent -

IATA/ICAO

- UN-no. -
- Proper Shipping Name -
- Class -
- PG* -

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product cf. Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

-

Additional information

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Seveso

-

Biocidal reg. no.

Not applicable

Sources

Council Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding.

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office,

According to EC-Regulation 2015/830

2002.

Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).

Regulation (EC) 1907/2006 (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H302 - Harmful if swallowed.

H318 - Causes serious eye damage.

H319 - Causes serious eye irritation.

H400 - Very toxic to aquatic life.

H410 - Very toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

-

Additional label elements

Not applicable

Other

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on:

The classification of the mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The safety data sheet is validated by

David Löwenstein

Date of last essential change (First cipher in SDS version)

-

Date of last minor change (Last cipher in SDS version)

-