

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Power Wash Antikim

Product no.

-

REACH registration number

Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Cleaning liquid

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

Blue & Green AB
Stenorsvägen 52
261 44 Landskrona
Sweden
Tfn: +46 418 399000
Fax: +46 418 13199
www.blueandgreen.se

E-mail

info@blueandgreen.se

SDS date

2020-10-08

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Skin Corr. 1B; H314
Eye Dam. 1; H318
Aquatic Acute 1; H400
Aquatic Chronic 2; H411
See full text of H-phrases in section 2.2.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Causes severe skin burns and eye damage. (H314)
Very toxic to aquatic life. (H400)

According to EC-Regulation 2015/830

Toxic to aquatic life with long lasting effects. (H411)

Precautionary statements

General If medical advice is needed, have product container or label at hand. (P101).
Keep out of reach of children. (P102).

Prevention Do not breathe mist/vapours/fume/spray. (P260).

Response IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. (P303+P361+P353).

Storage Store locked up. (P405).

Disposal Dispose of contents/container to an approved waste disposal plant. (P501).

Identity of the substances primarily responsible for the major health hazards

1-Heptanol, 2-propyl-, 8EO; potassium hydroxide; Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides

Additional labelling

Not applicable

Unique formula identifier (UFI)

PFJG-5KJT-N005-U2N2

2.3. Other hazards

Not applicable

Additional warnings

Tactile warning. If this product is sold in retail, it must be delivered with child-resistant fastening.

VOC (volatile organic compound)

Not applicable

SECTION 3: Composition/information on ingredients

3.1/3.2. Substances/Mixtures

NAME:	2-(2-ethoxyethoxy)ethanol
IDENTIFICATION NOS.:	CAS-no: 111-90-0 EC-no: 203-919-7 REACH-no: 01-2119475105-42
CONTENT:	5 - <10%
CLP CLASSIFICATION:	NA
NAME:	1-Heptanol, 2-propyl-, 8EO
IDENTIFICATION NOS.:	CAS-no: 160875-66-1
CONTENT:	5 - <10%
CLP CLASSIFICATION:	Acute Tox. 4, Eye Dam. 1 H302, H318
NAME:	potassium hydroxide
IDENTIFICATION NOS.:	CAS-no: 1310-58-3 EC-no: 215-181-3 REACH-no: 01-2119487136-33 Index-no: 019-002-00-8
CONTENT:	2.5 - <5%
CLP CLASSIFICATION:	Met. Corr. 1, Acute Tox. 4, Skin Corr. 1A H290, H302, H314
NAME:	Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides
IDENTIFICATION NOS.:	CAS-no: 68424-85-1 EC-no: 270-325-2 REACH-no: 01-2119965180-41
CONTENT:	2.5 - <5%
CLP CLASSIFICATION:	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1 H302, H314, H318, H400, H410 (M-acute = 10) (M-chronic = 1)

(*) See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

ATEmix(inhale, vapour) > 20
ATEmix(inhale, dust/mist) > 5
ATEmix(inhale, gas) > 20000
ATEmix(dermal) > 2000
ATEmix(oral) > 2000
Eye Cat. 1 Sum = Sum(Ci/S(G)CLi) = 2.9904 - 4.4856
Skin Cat. 2 Sum = Sum(Ci/S(G)CLi) = 8.992 - 13.488
N chronic (CAT 2) Sum = Sum(Ci/(M(chronic)ⁱ*25)*0.1*10^{CATi}) = > 1 - 1.2
N acute (CAT 1) Sum = Sum(Ci/M(acute)ⁱ*25) = > 1 - 1.2

Detergent:
5 - 15%: NON-IONIC SURFACTANTS
< 5%: BENZALKONIUM CHLORIDE

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service: Dial 0344 892 0111 (24 h service). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with soap and water.

Eye contact

Remove contact lenses. Flush eyes with plenty of water or salt water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing.

Ingestion

In the case of ingestion, contact a doctor immediately and bring the safety data sheet or label. If the person is conscious, give them water. DO NOT try to induce vomiting, unless this is recommended by a doctor. Hold head facing down to prevent vomit returning to the mouth and throat. Prevent shock by keeping the injured person warm and calm. Initiate immediate resuscitation if breathing stops. If unconscious, roll the injured person into recovery position. Call an ambulance.

Burns

Not applicable

4.2. Most important symptoms and effects, both acute and delayed

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, -irritations and burns in the respiratory organs -as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs.

Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned: Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Some metal oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances. Avoid inhalation of vapours from spilled material.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities. It is recommended to install waste collection trays to prevent emissions to the waste water system and surrounding environment.

6.3. Methods and material for containment and cleaning up

According to EC-Regulation 2015/830

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, storage of tobacco, consumption and storage of food or liquids are not allowed in the workrooms. It is recommended to install waste collection trays to prevent emissions to the waste water system and surrounding environment. See section on 'Exposure controls/personal protection' for information on personal protection. Avoid direct contact with the product.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Storage temperature

No data available.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL

potassium hydroxide

Long-term exposure limit (8-hour TWA reference period): - ppm | - mg/m³

Short-term exposure limit (15-minute reference period): - ppm | 2 mg/m³

DNEL / PNEC

DNEL (potassium hydroxide): 1mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - Workers

DNEL (potassium hydroxide): 1mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - General population

DNEL (2-(2-ethoxyethoxy)ethanol): 50 mg/kg bw/d

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (2-(2-ethoxyethoxy)ethanol): 37 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (2-(2-ethoxyethoxy)ethanol): 18 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - Workers

DNEL (2-(2-ethoxyethoxy)ethanol): 25 mg/kg bw/d

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-(2-ethoxyethoxy)ethanol): 18.3 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-(2-ethoxyethoxy)ethanol): 25 mg/kg bw/d

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-(2-ethoxyethoxy)ethanol): 9 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - General population

DNEL (Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides): 3.96 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides): 5.7 mg/kg bw/day

According to EC-Regulation 2015/830

Exposure: Dermal
Duration of Exposure: Long term – Systemic effects - Workers

DNEL (Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides): 1.64 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Systemic effects - General population

DNEL (Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides): 3.4 mg/kg/day
Exposure: Dermal
Duration of Exposure: Long term – Systemic effects - General population

DNEL (Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides): 3.4 mg/kg bw/day
Exposure: Oral
Duration of Exposure: Long term – Systemic effects - General population

PNEC (2-(2-ethoxyethoxy)ethanol): 0.74 mg/l
Exposure: Freshwater

PNEC (2-(2-ethoxyethoxy)ethanol): 0.074 mg/l
Exposure: Marine water

PNEC (2-(2-ethoxyethoxy)ethanol): 10 mg/l
Exposure: Intermittent release

PNEC (2-(2-ethoxyethoxy)ethanol): 500 mg/l
Exposure: Sewage Treatment Plant

PNEC (2-(2-ethoxyethoxy)ethanol): 2.47 mg/kg dw
Exposure: Freshwater sediment

PNEC (2-(2-ethoxyethoxy)ethanol): 0.247mg/kg dw
Exposure: Marine water sediment

PNEC (2-(2-ethoxyethoxy)ethanol): 0.15 mg/kg dw
Exposure: Soil

PNEC (Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides): 0.0009 mg/l
Exposure: Freshwater

PNEC (Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides): 0.00096 mg/l
Exposure: Marine water

PNEC (Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides): 0.4 mg/l
Exposure: Sewage Treatment Plant

PNEC (Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides): 12.27 mg/kg dw
Exposure: Freshwater sediment

PNEC (Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides): 13.09 mg/kg dw
Exposure: Marine water sediment

PNEC (Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides): 7 mg/kg dw
Exposure: Soil

8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

General recommendations

Observe general occupational hygiene standards.

Exposure scenarios

There is no appendix to this safety data sheet.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

Keep containment materials near the workplace. If possible, collect spillage during work.

According to EC-Regulation 2015/830

Individual protection measures, such as personal protective equipment



Generally

Use only CE marked protective equipment.

Respiratory Equipment

In case of spray application: Use mask with particle filter S/SL

Skin protection

Dedicated work clothing should be worn. Wear a protective suit in the event of prolonged periods of work with the product.

Hand protection

Household gloves

Breakthrough time: > 480 minutes (Class 6)

Eye protection

Wear safety glasses with side shields.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form	Liquid
Colour	Colourless
Odour	Mild
Odour threshold (ppm)	No data available.
pH	14
Viscosity (40°C)	No data available.
Density (g/cm ³)	1.2

Phase changes

Melting point (°C)	No data available.
Boiling point (°C)	No data available.
Vapour pressure	No data available.
Decomposition temperature (°C)	No data available.
Evaporation rate (n-butylacetate = 100)	No data available.

Data on fire and explosion hazards

Flash point (°C)	No data available.
Ignition (°C)	No data available.
Auto flammability (°C)	No data available.
Explosion limits (% v/v)	No data available.
Explosive properties	No data available.

Solubility

Solubility in water	Soluble
n-octanol/water coefficient	No data available.

9.2. Other information

Solubility in fat (g/L)	No data available.
-------------------------	--------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

10.3. Possibility of hazardous reactions

Nothing special

10.4. Conditions to avoid

Nothing special

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

According to EC-Regulation 2015/830

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Substance: Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides

Species: Rat

Test: LD50

Route of exposure: Oral

Result: 300-2000 mg/kg

Substance: Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides

Species: Rabbit

Test: LD50

Route of exposure: Dermal

Result: 3340 mg/kg

Substance: potassium hydroxide

Species: Rat

Test: LD50

Route of exposure: Oral

Result: 333.0

Substance: 1-Heptanol, 2-propyl-, 8EO

Species: Rat

Test: LD50

Route of exposure: Oral

Result: >300-2000 mg/kg

Substance: 2-(2-ethoxyethoxy)ethanol

Species: Mouse

Test: LD50

Route of exposure: Oral

Result: 6031 mg/kg

Substance: 2-(2-ethoxyethoxy)ethanol

Species: Rabbit

Test: LD50

Route of exposure: Dermal

Result: 9143 mg/kg

Substance: 2-(2-ethoxyethoxy)ethanol

Species: Rat

Test: LC0

Route of exposure: Inhalation

Result: 25 mg/m³

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Data on substance: Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides

Test: no guideline followed

Organism: Rabbit

Result: corrosive

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation

No data available.

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

No data available.

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

Long term effects

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce

According to EC-Regulation 2015/830

adverse effects to lungs, -irritations and burns in the respiratory organs -as well as coughing. Dermal contact and contact with the eye cause irreversible effects.
This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

SECTION 12: Ecological information

12.1. Toxicity

Substance: Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides
Species: Daphnia
Test: EC50
Duration: 48h
Result: 0.01-0.1 mg/l

Substance: Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides
Species: Algae
Test: EC50
Duration: 72h
Result: 0.01-0.1 mg/l

Substance: Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides
Species: Fish
Test: LC50
Duration: 96h
Result: 0.1-1 mg/l

Substance: Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides
Species: Algae
Test: NOEC
Duration: 72h
Result: 0.001-0.01 mg/l

Substance: potassium hydroxide
Species: Fish
Test: LC50
Duration: 96h
Result: 80mg/l

Substance: potassium hydroxide
Species: Daphnia
Test: EC50
Duration: 48h
Result: 40-240mg/l

Substance: 1-Heptanol, 2-propyl- , 8EO
Species: Fish
Test: LC50
Duration: 96h
Result: 10-100 mg/l

Substance: 1-Heptanol, 2-propyl- , 8EO
Species: Daphnia
Test: EC50
Duration: 48h
Result: 10-100 mg/l

Substance: 1-Heptanol, 2-propyl- , 8EO
Species: Algae
Test: EC50
Duration: 72h
Result: 10-100 mg/l

Substance: 1-Heptanol, 2-propyl- , 8EO
Species: Fish
Test: NOEC
Duration:
Result: >1 mg/l

Substance: 2-(2-ethoxyethoxy)ethanol
Species: Fish
Test: LC50
Duration: 96h
Result: 6010 mg/l

According to EC-Regulation 2015/830

Substance: 2-(2-ethoxyethoxy)ethanol
Species: Daphnia
Test: LC50
Duration: 48h
Result: 1982 mg/l

Substance: 2-(2-ethoxyethoxy)ethanol
Species: Algae
Test: EC50
Duration: 96h
Result: >100 mg/l

12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
Quaternary ammonium compounds,...	Yes	Closed Bottle Test	>60%
1-Heptanol, 2-propyl-, 8EO	Yes	Closed Bottle Test	>60%
2-(2-ethoxyethoxy)ethanol	Yes	CO2 Evolution Test	79.4%

12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BCF
Quaternary ammonium compounds,...	No	-1.93	No data available
1-Heptanol, 2-propyl-, 8EO	No	No data available	No data available
2-(2-ethoxyethoxy)ethanol	No	-0.54	3

12.4. Mobility in soil

Quaternary ammonium compounds,....: Log Koc= -1.449967, Calculated from LogPow ().
2-(2-ethoxyethoxy)ethanol: Log Koc= -0.349226, Calculated from LogPow ().

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.
This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

Waste

EWC code

-

Specific labelling

Not applicable

Contaminated packing

Contaminated packaging must be disposed of similarly to the product.

SECTION 14: Transport information

14.1 – 14.4

This product is within scope of the regulations of transport of dangerous goods.

ADR/RID

14.1. UN number	1760
14.2. UN proper shipping name	CORROSIVE LIQUID, N.O.S.
14.3. Transport hazard class(es)	8
14.4. Packing group	III
Notes	-
Tunnel restriction code	-

IMDG

UN-no.	1760
Proper Shipping Name	POTASSIUM HYDROXIDE SOLUTION
Class	8
PG*	III
EmS	F-A,S-B
MP**	-
Hazardous constituent	-

IATA/ICAO

UN-no.	1760
Proper Shipping Name	POTASSIUM HYDROXIDE SOLUTION
Class	8
PG*	III

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product cf. Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Demands for specific education

-

Additional information

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Seveso

Seveso III Part 1: E1

Biocidal reg. no.

Not applicable

Sources

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.
 The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.
 Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents.
 Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).
 Regulation (EC) 1907/2006 (REACH).
 The Control of Major Accident Hazards (COMAH) Regulations 2015.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H290 - May be corrosive to metals.
 H302 - Harmful if swallowed.
 H314 - Causes severe skin burns and eye damage.
 H318 - Causes serious eye damage.
 H400 - Very toxic to aquatic life.
 H410 - Very toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

-

Additional label elements

Not applicable

Other

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on:
 The classification of the mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)
 The classification of the mixture in regard of environmental hazards are in accordance with the calculation

According to EC-Regulation 2015/830

methods given by Regulation (EC) No. 1272/2008 (CLP)

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The safety data sheet is validated by

David Löwenstein

Date of last essential change

(First cipher in SDS version)

-

Date of last minor change

(Last cipher in SDS version)

-