

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Trouble Solver

Product no.

351

Unique formula identifier (UFI)

M57R-0JDD-MA9S-R2AE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Glue remover

Uses advised against

No special

1.3. Details of the supplier of the safety data sheet

Company and address

Blue & Green AB

Stenorsvägen 52

261 44 Landskrona

Sweden

+46 418 399000

www.blueandgreen.se

E-mail

info@blueandgreen.se

Revision

25-01-2022

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Eye Irrit. 2; H319, Causes serious eye irritation.

2.2. Label elements

Hazard pictogram(s)



Signal word

Warning

Hazard statement(s)

Causes serious eye irritation. (H319)

Safety statement(s)

General

Keep out of reach of children. (P102)

If medical advice is needed, have product container or label at hand. (P101)

Prevention

Wash hands thoroughly after handling. (P264)

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Wear eye protection/protective gloves. (P280)

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)

If eye irritation persists: Get medical advice/attention. (P337+P313)

Storage

-

Disposal

-

Hazardous substances

No special

2.3. Other hazards

Additional labelling

Not applicable

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
(2-methoxymethylethoxy)propanol	CAS No.: 34590-94-8 EC No.: 252-104-2 REACH: 01-2119450011-60 Index No.:	40-60%		[1]
2-(2-butoxyethoxy)ethanol	CAS No.: 112-34-5 EC No.: 203-961-6 REACH: 01-2119475104-44 Index No.: 603-096-00-8	15-25%	Eye Irrit. 2, H319	[1], [3]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit

[3] According to UK REACH, Annex XVII, the substance is subject to restrictions.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet.

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Upon irritation: rinse with water. In the event of continued irritation, seek medical assistance.

Eye contact

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Upon irritation of the eye: Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30°C) for at least 5 minutes and continue until irritation stops. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Not applicable

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: headache, dizziness, ringing in ears, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No specific requirements

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Use sand, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 on "Disposal considerations" in regard of handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

Room temperature 18 to 23°C

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

—
(2-methoxymethylethoxy)propanol

Long term exposure limit (8 hours) (ppm): 50

Long term exposure limit (8 hours) (mg/m³): 308

Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

—
2-(2-butoxyethoxy)ethanol

Long term exposure limit (8 hours) (ppm): 10

Long term exposure limit (8 hours) (mg/m³): 67,5

Short term exposure limit (15 minutes) (ppm): 15

Short term exposure limit (15 minutes) (mg/m³): 101,2

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

Product/substance	(2-methoxymethylethoxy)propanol
DNEL	283 mg/kg/day
Route of exposure	Dermal
Duration	Long term – Systemic effects - Workers

Product/substance	(2-methoxymethylethoxy)propanol
DNEL	308 mg/kg
Route of exposure	Inhalation
Duration	Long term – Systemic effects - Workers

Product/substance	(2-methoxymethylethoxy)propanol
DNEL	121 mg/kg/day
Route of exposure	Dermal
Duration	Long term – Systemic effects - General population

Product/substance	(2-methoxymethylethoxy)propanol
DNEL	37.2 mg/m ³
Route of exposure	Inhalation
Duration	Long term – Systemic effects - General population

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Product/substance	(2-methoxymethylethoxy)propanol
DNEL	36 mg/kg/day
Route of exposure	Oral
Duration	Long term – Systemic effects - General population

Product/substance	2-(2-butoxyethoxy)ethanol
DNEL	6,25 mg/kg/day
Route of exposure	Oral
Duration	Long term – Systemic effects - General population

Product/substance	2-(2-butoxyethoxy)ethanol
DNEL	101.2 mg/m ³
Route of exposure	Inhalation
Duration	Short term – Local effects - Workers

Product/substance	2-(2-butoxyethoxy)ethanol
DNEL	67.5 mg/m ³
Route of exposure	Inhalation
Duration	Long term – Local effects - Workers

PNEC

Product/substance	(2-methoxymethylethoxy)propanol
PNEC	19 mg/L
Route of exposure	Freshwater
Duration of Exposure	

Product/substance	(2-methoxymethylethoxy)propanol
PNEC	190 mg/L
Route of exposure	Intermittent release
Duration of Exposure	

Product/substance	(2-methoxymethylethoxy)propanol
PNEC	1.9 mg/L
Route of exposure	Marine water
Duration of Exposure	

Product/substance	(2-methoxymethylethoxy)propanol
PNEC	2.74 mg/kg
Route of exposure	Soil
Duration of Exposure	

Product/substance	(2-methoxymethylethoxy)propanol
PNEC	7.02 mg/kg
Route of exposure	Marine water sediment
Duration of Exposure	

Product/substance	(2-methoxymethylethoxy)propanol
PNEC	70.2 mg/kg
Route of exposure	Freshwater sediment

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Duration of Exposure

Product/substance	(2-methoxymethylethoxy)propanol
PNEC	4168 mg/L
Route of exposure	Sewage treatment plant
Duration of Exposure	

Product/substance	2-(2-butoxyethoxy)ethanol
PNEC	0.44 mg/kg dw
Route of exposure	Marine water sediment
Duration of Exposure	

Product/substance	2-(2-butoxyethoxy)ethanol
PNEC	4.4 mg/kg dw
Route of exposure	Freshwater sediment
Duration of Exposure	

Product/substance	2-(2-butoxyethoxy)ethanol
PNEC	0.11 mg/L
Route of exposure	Marine water
Duration of Exposure	

Product/substance	2-(2-butoxyethoxy)ethanol
PNEC	11 mg/L
Route of exposure	Intermittent release
Duration of Exposure	

Product/substance	2-(2-butoxyethoxy)ethanol
PNEC	0.32 mg/kg dw
Route of exposure	Soil
Duration of Exposure	

Product/substance	2-(2-butoxyethoxy)ethanol
PNEC	1.1 mg/L
Route of exposure	Freshwater
Duration of Exposure	

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

No specific requirements


Respiratory Equipment

No specific requirements


Skin protection

No specific requirements

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Butyl	-	> 480	EN374-2, EN374-3, EN388	

Eye protection

Type	Standards	
Safety glasses with side shields.	EN166	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Colourless

Odour / Odour threshold

Characteristic

pH

Testing not relevant or not possible due to nature of the product.

Density (g/cm³)

0.94

Kinematic viscosity

Testing not relevant or not possible due to nature of the product.

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

Testing not relevant or not possible due to nature of the product.

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

Testing not relevant or not possible due to nature of the product.

Vapour pressure

Testing not relevant or not possible due to nature of the product.

Relative vapour density

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Testing not relevant or not possible due to nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to nature of the product.

Data on fire and explosion hazards

Flash point (°C)

82 °C

Ignition (°C)

Testing not relevant or not possible due to nature of the product.

Auto flammability (°C)

Testing not relevant or not possible due to nature of the product.

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to nature of the product.

Solubility

Solubility in water

Insoluble

n-octanol/water coefficient

Testing not relevant or not possible due to nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to nature of the product.

9.2. Other information

Other physical and chemical parameters

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	(2-methoxymethylethoxy)propanol
Test method	
Species	Rat
Route of exposure	Oral
Test	LD50
Result	>5000 mg/kg
Other information	

Product/substance	(2-methoxymethylethoxy)propanol
Test method	
Species	Rabbit
Route of exposure	Dermal

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Test	LD50
Result	9510 mg/kg
Other information	
Product/substance	(2-methoxymethylethoxy)propanol
Test method	
Species	Rat
Route of exposure	Inhalation
Test	LC50
Result	3.35 mg/L
Other information	
Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Species	Rat
Route of exposure	Oral
Test	LD50
Result	>2000 mg/kg
Other information	
Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Species	Rabbit
Route of exposure	Dermal
Test	LD50
Result	2764 mg/kg
Other information	
Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Species	Rat
Route of exposure	Inhalation
Test	LC50
Result	>29 ppm
Other information	
Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Species	Mouse
Route of exposure	Oral
Test	LD50
Result	2410 mg/kg
Other information	
Skin corrosion/irritation	
Product/substance	2-(2-butoxyethoxy)ethanol
Test method	OECD 404
Species	Rabbit
Duration	
Result	No adverse effect observed (Not irritating)

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Other information

Serious eye damage/irritation

Product/substance	2-(2-butoxyethoxy)ethanol
Test method	OECD 404
Species	Rabbit
Duration	
Result	Adverse effect observed (Irritating)
Other information	

Causes serious eye irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Product/substance	2-(2-butoxyethoxy)ethanol
Test method	OECD 406
Species	Guinea pig
Result	No adverse effect observed (not sensitising)
Other information	

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: headache, dizziness, ringing in ears, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

Endocrine disrupting properties

No special

Other information

No special

SECTION 12: Ecological information

12.1. Toxicity

Product/substance	(2-methoxymethylethoxy)propanol
Test method	
Species	Algae, Pseudokirchneriella subcapitata

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Compartment	
Duration	72 hours
Test	EC50
Result	>969 mg/L
Other information	
Product/substance	(2-methoxymethylethoxy)propanol
Test method	
Species	Daphnia, Daphnia magna
Compartment	
Duration	22 d
Test	NOEC
Result	0.5 mg/L
Other information	
Product/substance	(2-methoxymethylethoxy)propanol
Test method	
Species	Daphnia, Daphnia magna
Compartment	
Duration	48 hours
Test	EC50
Result	1919 mg/L
Other information	
Product/substance	(2-methoxymethylethoxy)propanol
Test method	
Species	Fish, Poecilia reticulata
Compartment	
Duration	96 hours
Test	LC50
Result	>1000 mg/L
Other information	
Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Species	Fish, Leuciscus idus
Compartment	
Duration	96 hours
Test	LC50
Result	>100 mg/L
Other information	
Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Species	Algae, Scenedesmus subspicatus
Compartment	
Duration	96 hours
Test	EC50
Result	>100 mg/L
Other information	

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Species	Daphnia, Daphnia magna
Compartment	
Duration	48 hours
Test	EC50
Result	>100 mg/L
Other information	

12.2. Persistence and degradability

Product/substance	(2-methoxymethylethoxy)propanol
Biodegradable	Yes
Test method	OECD 301 F
Result	75%

Product/substance	2-(2-butoxyethoxy)ethanol
Biodegradable	Yes
Test method	OECD 301 E
Result	100%

12.3. Bioaccumulative potential

Product/substance	(2-methoxymethylethoxy)propanol
Test method	
Potential bioaccumulation	No
LogPow	0.0060
BCF	No data available
Other information	

Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Potential bioaccumulation	No
LogPow	1.0000
BCF	No data available
Other information	

12.4. Mobility in soil

(2-methoxymethylethoxy)propanol
LogKoc = 0.28, High mobility potential.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

No special

12.7. Other adverse effects

No special

SECTION 13: Disposal considerations

13.1. Waste treatment methods

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Product is covered by the regulations on hazardous waste.
 HP 4 - Irritant (skin irritation and eye damage)
 Dispose of contents/container to an approved waste disposal plant.
 Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

07 06 04* Other organic solvents, washing liquids and mother liquors

Specific labelling

Not applicable

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

14.1. - 14.4.

Not dangerous goods according to ADR, IATA and IMDG.

ADR/RID

Not applicable

IMDG

Not applicable

MARINE POLLUTANT

No

IATA

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements

SEVESO - Categories / dangerous substances

Not applicable

Additional information

Not applicable

Sources

The Health and Safety at Work etc. Act 1974 Regulations 2013.
 [3] According to UK REACH, Annex XVII, the substance is subject to restrictions.
 Regulation (EU) No 1357/2014 of 18 December 2014 on waste.
 CLP Regulation (EC) No 1272/2008, as retained and amended in UK law.
 EC-Regulation 1907/2006 (REACH), as amended by UK REACH Regulations SI 2019/758

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H319, Causes serious eye irritation.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit.
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVCB = Complex hydrocarbon substance
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

The safety data sheet is validated by

Åsa Möller

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en